

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**EXHIBIT 4 B – LOCATION SPECIFIC CRITERIA**

**BRIDGE A – S-12-77 over Fishing Creek – Chester County**

**BRIDGE B – S-12-141 over Rocky Creek – Chester County**

**BRIDGE C – SC 200 over Wateree Creek – Fairfield County**

**BRIDGE D – SC 9 (EBL) over Catawba River – Chester/Lancaster Counties**

**BRIDGE E – SC 200 over Cane Creek – Lancaster County**

**BRIDGE F – S-46-22 over Steele Creek – York County**

**BRIDGE G – S-46-64 over Allison Creek – York County**

**BRIDGE H – S-46-347 over Stony Fork Creek – York County**

**BRIDGE I – S-46-732 over Calabash Branch – York County**

**BRIDGE J – I-85 (SBL & NBL) over Norfolk Southern Railroad – Cherokee County**

**BRIDGE K – S-46-103 over Fishing Creek – York County**

**BRIDGE L – S-11-41 over Peoples Creek – Cherokee County**

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE A**

**ROUTE: S-12-77**

**CROSSING: FISHING CREEK**

**COUNTY: CHESTER**

**STRUCTURE NUMBER: 1270007700100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	698 feet
<b>End of Existing Bridge:</b>	356 feet
<b>Design Speed:</b>	40 mph
<b>Functional Classification:</b>	Rural Local Secondary
<b>Design ADT:</b>	384
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 11’-0” Lanes with 6’-0” Shoulders (2’-0” Paved Shoulders and 4’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

**New Construction**

- a. Surface – 150 psy HMA Surface Type C  
Intermediate – 200 psy HMA Intermediate Type C  
Base - 400 psy HMA Base Type B

**Existing Pavement**

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 150 psy HMA Surface Type C

Variable milling for pavement tie-ins as directed by SCDOT

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:**      Prestressed Concrete Girders  
   Structural Steel Rolled W Beams  
   Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 37'-3" (Includes 34'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:**      To be determined by hydraulic design.

**Miscellaneous Requirements**

No MSE walls will be permitted

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 405'-0" and minimum length of span over channel shall be 135'-0" as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA





EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves			
PIN No.   89094 BR01	File No.   12.09094.1	Latitude.   34.637	Designer:   M. Jackson - Midlands RPG
Route:   S-77	County:   Chester	Longitude:   80.9274	Date:   5/3/2011
Project:   S-77 over Fishing Creek			

Design EQ	PGA	S <sub>0.1</sub>	S <sub>0.2</sub>	M <sub>w</sub>	R (km)	Site Class	Damping
FEE	0.05	0.09	0.04			C	5%
SEE	0.14	0.22	0.12			C	

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface




FEE ADRS Curve  
Three-Point Method

T	S <sub>a</sub>
0.00	0.05
0.02	0.06
0.03	0.06
0.04	0.06
0.05	0.07
0.07	0.08
0.08	0.08
0.10	0.09
0.13	0.09
0.17	0.09
0.20	0.09
0.23	0.09
0.27	0.09
0.30	0.09
0.33	0.09
0.37	0.09
0.40	0.09
0.43	0.09
0.46	0.09
0.50	0.09
0.55	0.07
0.79	0.06
0.84	0.05
1.09	0.04
1.23	0.04
1.38	0.03
1.53	0.03
1.68	0.03
1.82	0.02
1.97	0.02
2.12	0.02
2.26	0.02
2.41	0.02
2.56	0.02
2.71	0.02
2.85	0.02
3.00	0.01

SEE ADRS Curve  
Three-Point Method

T	S <sub>a</sub>
0.00	0.14
0.02	0.15
0.04	0.17
0.05	0.18
0.07	0.19
0.08	0.20
0.10	0.21
0.13	0.22
0.17	0.22
0.20	0.22
0.23	0.22
0.27	0.22
0.30	0.22
0.33	0.22
0.37	0.22
0.40	0.22
0.43	0.22
0.46	0.22
0.50	0.22
0.55	0.17
0.79	0.14
0.84	0.12
1.11	0.10
1.26	0.09
1.40	0.08
1.55	0.07
1.69	0.07
1.84	0.06
1.98	0.06
2.13	0.05
2.27	0.05
2.42	0.05
2.56	0.04
2.71	0.04
2.85	0.04
3.00	0.04

# ROUTE S-12-77 OVER FISHING CREEK CHESTER COUNTY PRELIMINARY BRIDGE LAYOUT



Note: Drawing is not to scale

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE B**

**ROUTE: S-12-141**

**CROSSING: ROCKY CREEK**

**COUNTY: CHESTER**

**STRUCTURE NUMBER: 1270014100100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	155 feet
<b>End of Existing Bridge:</b>	194 feet
<b>Design Speed:</b>	40 mph
<b>Functional Classification:</b>	Rural Local - Secondary
<b>Design ADT:</b>	1,216
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 11’-0” Lanes with 6’-0” Shoulders (2’-0” Paved Shoulders and 4’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

**New Construction**

- a. Surface – 150 psy HMA Surface Type C
- Intermediate – 200 psy HMA Intermediate Type C
- Base - 400 psy HMA Base Type B

**Existing Pavement**

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 150 psy HMA Surface Type C

Variable milling for pavement tie-ins as directed by SCDOT

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department. In addition, flood stages along the Catawba River are controlled by Duke Energy and therefore will require completion of the Duke Energy Conveyance Permit Application and FERC notification.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 37'-3" (Includes 34'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 1/2" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout Requirements sketch.

Note: Minimum bridge length shall be 320'-0" and minimum lengths of spans in channel shall be 80'-0" as shown in the Preliminary Bridge Layout sketch.

**d) UTILITIES**

SCDOT has begun utility coordination efforts with the Town of Great Falls concerning the 8" sewer main currently attached to the existing S-141 Bridge over Rocky Creek. The individual NTP for Construction at Rocky Creek Bridge will not be available until 250 calendar days from Full Notice to Proceed.



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA







EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves			
PIN No: 80984 BR02	File No: 12.039094.2	Latitude: 34.557	Designer: M. Jackson - Midlands RPG
Route: S-141	County: Chester	Longitude: 80.9969	Date: 5/4/2011
Project: S-141 over Rocky Creek			

Design EQ	PGA	S <sub>0</sub>	S <sub>1</sub>	S <sub>2</sub>	M <sub>0</sub>	R (km)	Geologic Condition	Site Class	Damping
SEE	0.19	0.23	0.12	0.12	1,385	133.8	Hard Rock - Seismically Outcrop	C	3%


SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



FEE ADRS Curve Three-Point Method	
T	S <sub>a</sub>
0.00	0.05
0.02	0.06
0.03	0.07
0.05	0.07
0.07	0.08
0.08	0.08
0.10	0.08
0.12	0.09
0.20	0.09
0.23	0.09
0.28	0.09
0.31	0.09
0.35	0.09
0.38	0.09
0.39	0.09
0.42	0.09
0.45	0.09
0.46	0.08
0.49	0.08
0.52	0.08
0.64	0.07
0.67	0.07
0.68	0.07
0.68	0.06
1.08	0.04
1.23	0.04
1.38	0.03
1.52	0.03
1.67	0.03
1.82	0.02
1.97	0.02
2.11	0.02
2.26	0.02
2.41	0.02
2.56	0.02
2.70	0.02
2.85	0.02
3.00	0.01

SEE ADRS Curve Three-Point Method	
T	S <sub>a</sub>
0.00	0.15
0.02	0.16
0.03	0.17
0.05	0.19
0.07	0.20
0.08	0.21
0.10	0.21
0.12	0.22
0.20	0.23
0.23	0.23
0.28	0.23
0.31	0.23
0.35	0.23
0.38	0.23
0.39	0.23
0.42	0.23
0.45	0.23
0.46	0.23
0.49	0.23
0.52	0.23
0.64	0.19
0.67	0.19
0.68	0.19
0.68	0.15
1.08	0.11
1.23	0.10
1.38	0.09
1.52	0.09
1.67	0.07
1.82	0.06
1.97	0.06
2.11	0.06
2.26	0.06
2.41	0.05
2.56	0.05
2.70	0.05
2.85	0.04
3.00	0.04

# ROUTE S-12-141 OVER ROCKY CREEK CHESTER COUNTY PRELIMINARY BRIDGE LAYOUT



Note: Drawing is not to scale

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE C**

**ROUTE: SC 200**

**CROSSING: WATEREE CREEK**

**COUNTY: FAIRFIELD**

**STRUCTURE NUMBER: 2040020000500**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	688 feet
<b>End of Existing Bridge:</b>	1127 feet
<b>Design Speed:</b>	60 mph
<b>Functional Classification:</b>	Rural Minor Arterial
<b>Design ADT:</b>	2,465
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 10’-0” Shoulders (2’-0” Paved Shoulders and 8’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

New Construction

- a. Surface – 200 psy HMA Surface Type B
- Intermediate – 200 psy HMA Intermediate Type B
- Base - 450 psy HMA Base Type A

Existing Pavement

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 200 psy HMA Surface Type B

Variable milling for pavement tie-ins as directed by SCDOT

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone A based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 47'-3" (Includes 44'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 1/2" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length requirements as shown in Preliminary Bridge Layout sketch

Note: Minimum bridge length shall be 325'-0" as shown in the Preliminary Bridge Layout sketch.

Interior Bents are allowed within the channel for this location.



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA







EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves			
PIN No. 83094 BR03	File No. 20.039094.3	Latitude: 34.4916	Designer: M. Jackson - Midlands RFG
Route: SC 200	County: Fairfield	Longitude: 81.0765	Date: 3/4/2011
Project: SC 200 over Waterlee Creek			

Design EQ	PGA	$S_{0.1}$	$S_{0.2}$	$S_{0.5}$	$S_{1.0}$	$M_w$	R (km)	Geologic Condition	Site Class	Damping
FEE	0.05	0.09	0.04	0.04	0.04	7.385	132.8	Hard Rock, Basement Outcrop	C	5%
SEE	0.15	0.23	0.12	0.12	0.12	7.385	132.8	Hard Rock, Basement Outcrop	C	5%

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



T	$S_a$
0.00	0.05
0.02	0.06
0.03	0.07
0.05	0.07
0.07	0.08
0.08	0.08
0.10	0.09
0.13	0.09
0.16	0.09
0.20	0.09
0.25	0.09
0.28	0.09
0.31	0.09
0.33	0.09
0.35	0.09
0.38	0.09
0.42	0.09
0.45	0.09
0.48	0.09
0.52	0.09
0.64	0.07
0.78	0.06
0.83	0.05
1.05	0.04
1.33	0.04
1.52	0.03
1.69	0.03
1.82	0.02
1.97	0.02
2.11	0.02
2.26	0.02
2.41	0.02
2.56	0.02
2.70	0.02
2.85	0.02
3.00	0.01

T	$S_a$
0.00	0.15
0.02	0.16
0.03	0.17
0.05	0.19
0.07	0.20
0.08	0.21
0.10	0.22
0.13	0.23
0.16	0.23
0.20	0.23
0.25	0.23
0.28	0.23
0.31	0.23
0.33	0.23
0.35	0.23
0.38	0.23
0.42	0.23
0.45	0.23
0.48	0.23
0.52	0.23
0.64	0.18
0.78	0.15
0.83	0.12
1.05	0.11
1.33	0.11
1.52	0.08
1.69	0.08
1.82	0.07
1.97	0.06
2.11	0.06
2.26	0.05
2.41	0.05
2.56	0.05
2.70	0.04
2.85	0.04
3.00	0.04






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE D**

**ROUTE: SC 9 EAST BOUND LANE**

**CROSSING: CATAWBA RIVER**

**COUNTY: CHESTER/LANCASTER**

**STRUCTURE NUMBER: 2940000920100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	330 feet
<b>End of Existing Bridge:</b>	1505 feet
<b>Design Speed:</b>	60 mph
<b>Functional Classification:</b>	Rural Minor Arterial
<b>Design ADT:</b>	8,825
<b>Terrain</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition but does not include maintenance of traffic lane shift lengths.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 10’-0” Shoulders (2’-0” Paved Shoulders and 8’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic for both eastbound and westbound will be maintained on the existing westbound bridge during construction (one lane in each direction divided by a temporary concrete barrier). See traffic control special provisions.

Temporary concrete barrier wall placed in the center of the bridge for separating two-way traffic shall ~~does not~~ require anchorage to the bridge deck.

**Pavement Design**

**New Construction**

- Surface – 200 psy HMA Surface Type B
- Intermediate – 200 psy HMA Surface Type B
- Base - 1200 psy HMA Base Type A

**Existing Pavement**

- 14” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.
- Overlay –200 psy HMA Surface Type B
- Variable milling for pavement tie-ins as directed by SCDOT

## EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

Temporary Pavement (median crossovers)  
Surface – 200 psy HMA Surface Type B  
Intermediate – 200 psy HMA Surface Type B  
Base – 800 psy HMA Base Type A

### b) HYDROLOGY

The project site is located in a FEMA Special Flood Hazard Area Zone A based on latest maps reviewed by Department. In addition, flood stages along the Catawba River are controlled by Duke Energy and therefore will require completion of the Duke Energy Conveyance Permit Application and FERC notification.

Low Chord elevation of the new bridge shall be equal to or greater than the low chord elevation, at mid span, of the beams on the westbound bridge.

### c) STRUCTURE

#### Bridge Design Criteria

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 47'-3" (Includes 44'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

#### Miscellaneous Requirements

The use of MSE walls as bridge abutments will not be allowed for this bridge.

#### Seismic Design Criteria

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

#### General Bridge Layout Requirements

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch. The proposed eastbound bridge span arrangement shall match the existing westbound bridge span arrangement within the limits of the Catawba River overbanks. No offset will be allowed.

Note: Minimum bridge length shall be 1424'-6" and should closely match the length of West bound lane bridge as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA


SC Seismic Hazard Map Three-Point ADRS Curves

PIN No. 39084 BR04	File No. 1129.039094.4	Latitude: 34.7067
Route: SC 9	County: Chester/Lancaster	Longitude: 80.8668
Project: SC 9 over Catawba River		

Designer: M. Jackson - Midlands RPG
Date: 5/19/2011

Design EQ	PGA	$S_{int}$	$S_{vs}$	$M_w$	R (km)	Geologic Condition	Site Class	Damping
FEE	0.07	0.11	0.06	7.345	189.25	Hard Rock-Basement Outcrop	D	5%
SEE	0.18	0.28	0.16	7.38	188.2	Hard Rock-Basement Outcrop	D	

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



FEE ADRS Curve Three-Point Method		SEE ADRS Curve Three-Point Method	
T	$S_a$	T	$S_a$
0.00	0.07	0.00	0.18
0.02	0.08	0.02	0.19
0.04	0.08	0.04	0.21
0.05	0.09	0.06	0.23
0.07	0.10	0.08	0.25
0.09	0.11	0.09	0.25
0.11	0.11	0.11	0.25
0.14	0.11	0.15	0.25
0.18	0.11	0.19	0.25
0.21	0.11	0.23	0.25
0.25	0.11	0.26	0.25
0.32	0.11	0.34	0.25
0.36	0.11	0.38	0.25
0.39	0.11	0.42	0.25
0.43	0.11	0.45	0.25
0.46	0.11	0.49	0.25
0.50	0.11	0.53	0.25
0.54	0.11	0.57	0.25
0.68	0.09	0.71	0.22
0.83	0.07	0.85	0.19
1.00	0.06	1.04	0.18
1.22	0.05	1.24	0.18
1.26	0.05	1.28	0.12
1.41	0.04	1.43	0.11
1.55	0.04	1.57	0.10
1.70	0.04	1.71	0.09
1.84	0.03	1.85	0.09
1.89	0.03	2.00	0.09
2.13	0.03	2.14	0.07
2.28	0.03	2.28	0.07
2.47	0.02	2.47	0.06
2.71	0.02	2.71	0.05
2.86	0.02	2.86	0.05
3.00	0.02	3.00	0.05




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE E**

**ROUTE: SC 200**

**CROSSING: CANE CREEK**

**COUNTY: LANCASTER**

**STRUCTURE NUMBER: 2940020000500**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	653 feet
<b>End of Existing Bridge:</b>	791 feet
<b>Design Speed:</b>	60 mph
<b>Functional Classification:</b>	Rural Major Collector
<b>Design ADT:</b>	4,088
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 10’-0” Shoulders (2’-0” Paved Shoulders and 8’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on new alignment downstream of the existing structure. Two lanes of traffic (one lane in each direction) will be maintained on the existing bridge during construction.

**Pavement Design**

**New Construction**

- Surface – 175 psy HMA Surface Type C
- Intermediate – 200 psy HMA Surface Type C
- Base - 700 psy HMA Base Type A
- Alternate Base – 10 inch Graded Aggregate Base

**Existing Pavement**

- 12” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.
- Overlay – 175 psy HMA Surface Type C
- Variable milling for pavement tie-ins as directed by SCDOT



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone A based on latest maps reviewed by Department, and is designated as having a “high” risk for flooding.

Cane Creek at SC 200 is listed on the SCDHEC 303(d) list for impaired waters and therefore stormwater control measures for sensitive waters must be in accordance with SCDOT’s MS4 Permit.

It is anticipated that there will be more than 300 feet of stream impacts on this project and an Individual Permit from the US Army Corp of Engineers will be required.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**  
The minimum outside deck width shall be 47’-3” (Includes 44’-0” Clear Roadway Width, Two -- 1’-6” Barrier Parapets, and Two -- 1 ½” Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 180’-0 as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA


**SC Seismic Hazard Map  
Three-Point ADRS Curves**

PIN No. 130094 BR05	File No. 29.03094.5	Latitude: 34.7978
Route: SC 200	County: Lancaster	Longitude: 80.7462
Project: SC 200 Over Cane Creek		

Design EQ	PGA	S <sub>v</sub>	S <sub>h</sub>	M <sub>v</sub>	R (km)	Geologic Condition	Site Class	Damping
FEE	0.05	0.09	0.04	7.365	136.55	Hard Rock- Basement Outcrop	C	5%
SEE	0.13	0.20	0.11	7.37	136.35	Hard Rock- Basement Outcrop	C	

Designer: M. Jackson - Midlands RPG	Date: 5/13/2011
-------------------------------------	-----------------

FEE ADRS Curve Three-Point Method		SEE ADRS Curve Three-Point Method	
T	S <sub>a</sub>	T	S <sub>a</sub>
0.0	0.05	0.0	0.13
0.02	0.05	0.02	0.14
0.03	0.06	0.04	0.15
0.05	0.06	0.05	0.16
0.07	0.07	0.07	0.18
0.09	0.08	0.09	0.19
0.10	0.08	0.10	0.20
0.14	0.08	0.15	0.20
0.17	0.08	0.18	0.20
0.21	0.08	0.22	0.20
0.24	0.08	0.25	0.20
0.26	0.08	0.28	0.20
0.28	0.08	0.30	0.20
0.35	0.08	0.35	0.20
0.38	0.08	0.40	0.20
0.42	0.08	0.44	0.20
0.45	0.08	0.47	0.20
0.49	0.08	0.51	0.20
0.52	0.08	0.55	0.20
0.57	0.06	0.63	0.16
0.61	0.05	0.63	0.13
0.66	0.04	0.65	0.11
1.05	0.03	1.12	0.08
1.40	0.03	1.41	0.08
1.54	0.03	1.55	0.07
1.69	0.03	1.70	0.06
1.83	0.02	1.85	0.06
1.98	0.02	1.93	0.06
2.12	0.02	2.13	0.05
2.27	0.02	2.28	0.05
2.42	0.02	2.42	0.05
2.57	0.02	2.57	0.04
2.85	0.01	2.85	0.04
3.00	0.01	3.00	0.04






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE F**

**ROUTE: S-46-22**

**CROSSING: STEELE CREEK**

**COUNTY: YORK**

**STRUCTURE NUMBER: 4670002200300**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	1390 feet
<b>End of Existing Bridge:</b>	731 feet
<b>Design Speed:</b>	40 mph
<b>Functional Classification:</b>	Urban Collector
<b>Design ADT:</b>	13,800
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 8’-0” Shoulders (2’-0” Paved Shoulders and 6’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on new alignment downstream of the existing structure. Two lanes of traffic (one lane in each direction) will be maintained on the existing bridge during construction.

**Pavement Design**

New Construction

Surface – 200 psy HMA Surface Type B

Intermediate – 200 psy HMA Surface Type B

Base - 700 psy HMA Base Type A

Alternate Base – 10 inch Graded Aggregate Base plus extra 200 psy HMA Surface B

Existing Pavement

12” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 200 psy HMA Surface Type B

Variable milling for pavement tie-ins as directed by SCDOT

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**b) HYDROLOGY**

The project site is not located in a FEMA Special Flood Hazard Zone AE with a Designated Floodway based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 43'-3" (Includes 40'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

Steele Creek is listed on the SCDHEC 303(d) list for impaired waters and therefore stormwater control measures for sensitive waters must be in accordance with SCDOT's MS4 Permit.

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 330'-0" and minimum length of span over channel shall be 70'-0" over the main channel and 75'-0" over the unnamed tributary as shown in the Preliminary Bridge Layout sketch.



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA







EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves

File No: 146.039094.7  
 Route: S22  
 Project: S22 over Steel Creek  
 Latitude: 85.0894  
 Longitude: 80.9642  
 Designer: M. Jackson - Midlands RPG  
 Date: 5/17/2011

Design EQ	PGA	S <sub>0%</sub>	S <sub>5%</sub>	M <sub>w</sub>	R (km)	Geologic Condition	Site Class	Damping
FEE	0.04	0.08	0.04	7.365	83	Hard Rock, Basement Outcrop	C	5%
SEE	0.11	0.17	0.10	7.37	182.36	Hard Rock, Basement Outcrop	C	5%

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



FEE ADRS Curve Three-Point Method

T	S <sub>a</sub>
0.00	0.04
0.02	0.05
0.04	0.05
0.05	0.06
0.07	0.07
0.09	0.07
0.11	0.08
0.15	0.08
0.20	0.08
0.25	0.08
0.30	0.08
0.32	0.08
0.36	0.08
0.40	0.08
0.43	0.08
0.47	0.08
0.50	0.08
0.54	0.08
0.57	0.08
0.60	0.08
0.65	0.08
0.70	0.08
0.75	0.08
0.80	0.08
0.85	0.08
0.90	0.08
0.95	0.08
1.00	0.08
1.10	0.08
1.20	0.08
1.28	0.08
1.41	0.08
1.55	0.08
1.70	0.08
1.84	0.08
1.99	0.08
2.13	0.08
2.28	0.08
2.42	0.08
2.57	0.08
2.71	0.08
2.86	0.08
3.00	0.08


SEE ADRS Curve Three-Point Method

T	S <sub>a</sub>
0.00	0.11
0.02	0.12
0.04	0.13
0.05	0.14
0.07	0.15
0.09	0.16
0.11	0.17
0.15	0.17
0.20	0.17
0.25	0.17
0.30	0.17
0.32	0.17
0.36	0.17
0.40	0.17
0.43	0.17
0.47	0.17
0.50	0.17
0.54	0.17
0.57	0.17
0.60	0.17
0.65	0.17
0.70	0.17
0.75	0.17
0.80	0.17
0.85	0.17
0.90	0.17
0.95	0.17
1.00	0.17
1.10	0.17
1.20	0.17
1.28	0.17
1.41	0.17
1.55	0.17
1.70	0.17
1.84	0.17
1.99	0.17
2.13	0.17
2.28	0.17
2.42	0.17
2.57	0.17
2.71	0.17
2.86	0.17
3.00	0.17

ROUTE S-46-22 OVER STEELE CREEK

YORK COUNTY

PRELIMINARY BRIDGE LAYOUT



Note: Drawing is not to scale

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE G**

**ROUTE: S-46-64**

**CROSSING: ALLISON CREEK**

**COUNTY: YORK**

**STRUCTURE NUMBER: 4670006400200**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	444 feet
<b>End of Existing Bridge:</b>	441 feet
<b>Design Speed:</b>	50 mph
<b>Functional Classification:</b>	Rural Major Collector
<b>Design ADT:</b>	2,700
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 8’-0” Shoulders (2’-0” Paved Shoulders and 6’-0” Grassed Shoulders)

**Miscellaneous Requirements**

Approach lengths extend the bridge replacement project limits beyond the intersection of S-46-64 and S-46-732. Any improvements necessary for the intersection are dictated by the Highway Design Manual.

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed. Note that S-46-732 will be used as part of the detour route during the construction of the bridge on S-46-64 over Allison Creek. Alternately, S-46-64 will be used as part of the detour route during the construction of the bridge on S-46-732 over Calabash Branch. Therefore, both bridges cannot be closed for construction simultaneously. One must remain open to traffic at all times.

**Pavement Design**

New Construction

Surface – 175 psy HMA Surface Type C

Intermediate – 250 psy HMA Intermediate Type C

Base - 450 psy HMA Base Type A

## EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

### Existing Pavement

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 175 psy HMA Surface Type C

Variable milling for pavement tie-ins as directed by SCDOT

### b) HYDROLOGY

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

### c) STRUCTURE

#### Bridge Design Criteria

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders  
Cast-In- Place Concrete Flat Slabs  
Precast Concrete Cored Slabs  
Precast Concrete Solid Slabs

#### Minimum Outside Deck Width:

If Prestressed Concrete Cored Slabs and/or Prestressed Concrete Solid Slabs are used, then the minimum outside deck width shall be 42’-0” (Includes 38’-10” Clear Roadway Width, Two -- 1’-6” Barrier Parapets, and Two -- 1” Slab Extensions for Slip Forming Barriers)

If Prestressed Concrete Girders, Structural Steel Rolled W Beams, Structural Steel Welded Plate Girders, or Flat Slabs are used, then the minimum outside deck width shall be 43’-3” (Includes 40’-0” Clear Roadway Width, Two -- 1’-6” Barrier Parapets, and Two -- 1 ½” Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

#### Miscellaneous Requirements

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

#### Seismic Design Criteria

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

#### General Bridge Layout Requirements

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 220'-0" and minimum length of span over channel shall be 60'-0" as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA







EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves

File No: 46 038034.8	Latitude: 35.0663	Designer: M. Jackson - Midlands RPG
Route: S-64	Longitude: 81.1902	Date: 5/17/2011
Project: S-64 over Allison Creek		


Design EQ	PGA	S <sub>1</sub>	S <sub>2</sub>	M <sub>1</sub>	R (km)	Geologic Condition	Site Class	Damping
FEE	0.08	0.10	0.08	7.315	207.45	Hard Rock, Basement Outcrop	D	5%
SEE	0.15	0.23	0.14	7.375	203.8	Hard Rock, Basement Outcrop	D	5%

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



FEE ADRS Curve Three-Point Method		SEE ADRS Curve Three-Point Method	
T	S <sub>a</sub>	T	S <sub>a</sub>
0.00	0.00	0.00	0.15
0.02	0.02	0.02	0.15
0.04	0.04	0.04	0.15
0.06	0.06	0.06	0.15
0.08	0.08	0.08	0.15
0.10	0.10	0.10	0.15
0.12	0.11	0.12	0.15
0.14	0.11	0.14	0.15
0.16	0.11	0.16	0.15
0.18	0.11	0.18	0.15
0.20	0.11	0.20	0.15
0.22	0.11	0.22	0.15
0.24	0.11	0.24	0.15
0.26	0.11	0.26	0.15
0.28	0.11	0.28	0.15
0.30	0.11	0.30	0.15
0.32	0.11	0.32	0.15
0.34	0.11	0.34	0.15
0.36	0.11	0.36	0.15
0.38	0.11	0.38	0.15
0.40	0.11	0.40	0.15
0.42	0.11	0.42	0.15
0.44	0.11	0.44	0.15
0.46	0.11	0.46	0.15
0.48	0.11	0.48	0.15
0.50	0.11	0.50	0.15
0.52	0.11	0.52	0.15
0.54	0.11	0.54	0.15
0.56	0.11	0.56	0.15
0.58	0.11	0.58	0.15
0.60	0.11	0.60	0.15
0.62	0.11	0.62	0.15
0.64	0.11	0.64	0.15
0.66	0.11	0.66	0.15
0.68	0.11	0.68	0.15
0.70	0.11	0.70	0.15
0.72	0.11	0.72	0.15
0.74	0.11	0.74	0.15
0.76	0.11	0.76	0.15
0.78	0.11	0.78	0.15
0.80	0.11	0.80	0.15
0.82	0.11	0.82	0.15
0.84	0.11	0.84	0.15
0.86	0.11	0.86	0.15
0.88	0.11	0.88	0.15
0.90	0.11	0.90	0.15
0.92	0.11	0.92	0.15
0.94	0.11	0.94	0.15
0.96	0.11	0.96	0.15
0.98	0.11	0.98	0.15
1.00	0.11	1.00	0.15
1.02	0.11	1.02	0.15
1.04	0.11	1.04	0.15
1.06	0.11	1.06	0.15
1.08	0.11	1.08	0.15
1.10	0.11	1.10	0.15
1.12	0.11	1.12	0.15
1.14	0.11	1.14	0.15
1.16	0.11	1.16	0.15
1.18	0.11	1.18	0.15
1.20	0.11	1.20	0.15
1.22	0.11	1.22	0.15
1.24	0.11	1.24	0.15
1.26	0.11	1.26	0.15
1.28	0.11	1.28	0.15
1.30	0.11	1.30	0.15
1.32	0.11	1.32	0.15
1.34	0.11	1.34	0.15
1.36	0.11	1.36	0.15
1.38	0.11	1.38	0.15
1.40	0.11	1.40	0.15
1.42	0.11	1.42	0.15
1.44	0.11	1.44	0.15
1.46	0.11	1.46	0.15
1.48	0.11	1.48	0.15
1.50	0.11	1.50	0.15
1.52	0.11	1.52	0.15
1.54	0.11	1.54	0.15
1.56	0.11	1.56	0.15
1.58	0.11	1.58	0.15
1.60	0.11	1.60	0.15
1.62	0.11	1.62	0.15
1.64	0.11	1.64	0.15
1.66	0.11	1.66	0.15
1.68	0.11	1.68	0.15
1.70	0.11	1.70	0.15
1.72	0.11	1.72	0.15
1.74	0.11	1.74	0.15
1.76	0.11	1.76	0.15
1.78	0.11	1.78	0.15
1.80	0.11	1.80	0.15
1.82	0.11	1.82	0.15
1.84	0.11	1.84	0.15
1.86	0.11	1.86	0.15
1.88	0.11	1.88	0.15
1.90	0.11	1.90	0.15
1.92	0.11	1.92	0.15
1.94	0.11	1.94	0.15
1.96	0.11	1.96	0.15
1.98	0.11	1.98	0.15
2.00	0.11	2.00	0.15
2.02	0.11	2.02	0.15
2.04	0.11	2.04	0.15
2.06	0.11	2.06	0.15
2.08	0.11	2.08	0.15
2.10	0.11	2.10	0.15
2.12	0.11	2.12	0.15
2.14	0.11	2.14	0.15
2.16	0.11	2.16	0.15
2.18	0.11	2.18	0.15
2.20	0.11	2.20	0.15
2.22	0.11	2.22	0.15
2.24	0.11	2.24	0.15
2.26	0.11	2.26	0.15
2.28	0.11	2.28	0.15
2.30	0.11	2.30	0.15
2.32	0.11	2.32	0.15
2.34	0.11	2.34	0.15
2.36	0.11	2.36	0.15
2.38	0.11	2.38	0.15
2.40	0.11	2.40	0.15
2.42	0.11	2.42	0.15
2.44	0.11	2.44	0.15
2.46	0.11	2.46	0.15
2.48	0.11	2.48	0.15
2.50	0.11	2.50	0.15
2.52	0.11	2.52	0.15
2.54	0.11	2.54	0.15
2.56	0.11	2.56	0.15
2.58	0.11	2.58	0.15
2.60	0.11	2.60	0.15
2.62	0.11	2.62	0.15
2.64	0.11	2.64	0.15
2.66	0.11	2.66	0.15
2.68	0.11	2.68	0.15
2.70	0.11	2.70	0.15
2.72	0.11	2.72	0.15
2.74	0.11	2.74	0.15
2.76	0.11	2.76	0.15
2.78	0.11	2.78	0.15
2.80	0.11	2.80	0.15
2.82	0.11	2.82	0.15
2.84	0.11	2.84	0.15
2.86	0.11	2.86	0.15
2.88	0.11	2.88	0.15
2.90	0.11	2.90	0.15
2.92	0.11	2.92	0.15
2.94	0.11	2.94	0.15
2.96	0.11	2.96	0.15
2.98	0.11	2.98	0.15
3.00	0.11	3.00	0.15

**ROUTE S-46-64 OVER ALLISON CREEK  
YORK COUNTY  
PRELIMINARY BRIDGE LAYOUT**



*Note: Drawing is not to scale*

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE H**

**ROUTE: S-46-347**

**CROSSING: STONY FORK CREEK**

**COUNTY: YORK**

**STRUCTURE NUMBER: 4670034700100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	504 feet
<b>End of Existing Bridge:</b>	955 feet
<b>Design Speed:</b>	50 mph
<b>Functional Classification:</b>	Rural Major Collector
<b>Design ADT:</b>	1,800
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 11'-0" Lanes with 6'-0" Shoulders (2'-0" Paved Shoulders and 4'-0" Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

New Construction

- Surface – 175 psy HMA Surface Type C
- Intermediate – 200 psy HMA Intermediate Type C
- Base - 450 psy HMA Base Type B

Existing Pavement

- 8" of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.
- Overlay – 175 psy HMA Surface Type C
- Variable milling for pavement tie-ins as directed by SCDOT

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders  
Cast-In-Place Concrete Flat Slabs  
Prestressed Concrete Cored Slabs  
Prestressed Concrete Solid Slabs

**Minimum Outside Deck Width:**

If Prestressed Concrete Cored Slabs and/or Prestressed Concrete Solid Slabs are used, then the minimum outside deck width shall be 36'-0" (Includes 32'-10" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1" Slab Extensions for Slip Forming Barriers)

If Prestressed Concrete Girders, Structural Steel Rolled W Beams, Structural Steel Welded Plate Girders, or Flat Slabs are used, then the minimum outside deck width shall be 37'-3" (Includes 34'-0" Clear Roadway Width, Two -- 1'-6" Barrier Parapets, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 90'-0" ~~100'-0"~~ and minimum length of span over channel shall be 70'-0" as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA









EXHIBIT 4B – LOCATION SPECIFIC CRITERIA



ROUTE S-46-347 OVER STONY FORK CREEK  
YORK COUNTY  
PRELIMINARY BRIDGE LAYOUT

SUBJECT TO CHANGE BASED ON DESIGN



Note: Drawing is not to scale

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE I**

**ROUTE: S-46-732**

**CROSSING: CALABASH BRANCH**

**COUNTY: YORK**

**STRUCTURE NUMBER: 4670073200100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	233 feet
<b>End of Existing Bridge:</b>	To intersection with S-46-64
<b>Design Speed:</b>	45 mph
<b>Functional Classification:</b>	Rural Local
<b>Design ADT:</b>	1,000
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 11’-0” Lanes with 6’-0” Shoulders (2’-0” Paved Shoulders and 4’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed. Note that S-46-732 will be used as part of the detour route during the construction of the bridge on S-46-64 over Allison Creek. Alternately, S-46-64 will be used as part of the detour route during the construction of the bridge on S-46-732 over Calabash Branch. Therefore, both bridges cannot be closed for construction simultaneously. One must remain open to traffic at all times.

Reclaim approximately 1.1 miles of S-46-732 from Jim McCarter Road to the start of the bridge approach (233 feet from beginning of existing bridge).

**Pavement Design**

New Construction

Surface – 150 psy HMA Surface Type C

Intermediate – 200 psy HMA Intermediate Type C

Base - 400 psy HMA Base Type B

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

Existing Pavement

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 150 psy HMA Surface Type C

S-732 Reclamation

8” Reclamation as directed by SCDOT with 150 psy HMA Surface Type C. Reclaim 1.1 miles of S-732 from Jim McCarter Road to the start of the bridge approach at a width of 24’

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders  
Cast-In-Place Concrete Flat Slabs  
Prestressed Concrete Cored Slabs  
Prestressed Concrete Solid Slabs

**Minimum Outside Deck Width:**

If Prestressed Concrete Cored Slabs and/or Prestressed Concrete Solid Slabs are used, then the minimum outside deck width shall be 36’-0” (Includes 32’-10” Clear Roadway Width, Two -- 1’-6” Barrier Parapets, and Two -- 1” Slab Extensions for Slip Forming Barriers)

If Prestressed Concrete Girders, Structural Steel Rolled W Beams, Structural Steel Welded Plate Girders, or Flat Slabs are used, then the minimum outside deck width shall be 37’-3” (Includes 34’-0” Clear Roadway Width, Two -- 1’-6” Barrier Parapets, and Two -- 1 ½” Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 140'-0" and minimum length of span over channel shall be 60'-0" as shown in the Preliminary Bridge Layout sketch.

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA





EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

SC Seismic Hazard Map Three-Point ADRS Curves			
PIN No. 39094 BR10	File No. 46.039094.10	Latitude: 35.0678	Designer: M. Jackson - Midlands R/P
Route: S-732	County: York	Longitude: 81.1903	Date: 5/17/2011
Project: S-732 over Calabash Branch			

Design EQ	PGA	S <sub>01</sub>	S <sub>02</sub>	M <sub>w</sub>	R (km)	Geologic Condition	Site Class	Damping
FEE	0.08	0.10	0.06	7.335	209.5	Hard Rock/Basement Outcrop	D	5%
SEE	0.15	0.23	0.14	7.315	207.95	Hard Rock/Basement Outcrop	D	5%

SC Seismic Hazard Map Three-Point ADRS Curve From Ground Surface



FEE ADRS Curve Three-Point Method



T	S <sub>a</sub>
0.00	0.06
0.02	0.07
0.04	0.08
0.06	0.09
0.07	0.09
0.08	0.10
0.10	0.11
0.15	0.10
0.19	0.10
0.22	0.10
0.26	0.10
0.30	0.10
0.37	0.10
0.41	0.10
0.45	0.10
0.49	0.10
0.52	0.10
0.56	0.10
0.70	0.08
0.85	0.07
0.98	0.06
1.14	0.05
1.28	0.05
1.42	0.04
1.57	0.04
1.73	0.03
1.85	0.03
2.00	0.03
2.14	0.03
2.29	0.03
2.43	0.02
2.57	0.02
2.71	0.02
2.86	0.02
3.00	0.02

SEE ADRS Curve Three-Point Method

T	S <sub>a</sub>
0.00	0.15
0.02	0.16
0.04	0.18
0.06	0.19
0.07	0.20
0.08	0.20
0.10	0.22
0.15	0.23
0.19	0.23
0.22	0.24
0.26	0.25
0.30	0.25
0.37	0.25
0.41	0.25
0.45	0.25
0.49	0.25
0.52	0.25
0.56	0.25
0.70	0.18
0.85	0.16
0.98	0.14
1.14	0.12
1.28	0.11
1.42	0.10
1.57	0.09
1.73	0.08
1.85	0.07
2.00	0.07
2.14	0.06
2.29	0.06
2.43	0.05
2.57	0.05
2.71	0.05
2.86	0.05
3.00	0.05

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

ROUTE S-46-732 OVER CALABASH BRANCH  
YORK COUNTY  
PRELIMINARY BRIDGE LAYOUT



Note: Drawing is not to scale

EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE J**

**ROUTE: I-85 North Bound and South Bound Lanes**

**CROSSING: NORFOLK SOUTHERN RAILROAD**

**COUNTY: CHEROKEE**

**STRUCTURE NUMBER: 1110008510500 & 1110008530500**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	Length is based on design
<b>End of Existing Bridge:</b>	Length is based on design
<b>Design Speed:</b>	65 mph
<b>Functional Classification:</b>	Rural Freeway
<b>Design ADT:</b>	36,575
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length does not include transition from project design criteria to existing condition. The transition length required outside of the minimum approach length (based on design) does not have to meet geometric design criteria but shall not degrade the existing facility.*

**Typical Section**

Roadway Approaches will consist of 4 – 12’-0” Lanes (2 Lanes for North Bound Traffic and 2 Lanes for South Bound Traffic) with 12’-0” Outside Shoulders (10’-0” Paved Shoulders and 2’-0” Grassed Shoulders) and 10’-0” Inside Shoulders (4’-0” Paved Shoulders and 6’-0” Grassed Shoulders). North Bound and South Bound Traffic will be separated by barrier as specified in the Highway Design Manual.

**Maintenance of Traffic**

The two existing bridges will be replaced with one structure. The proposed bridge will be constructed on new alignment north of the existing structure. Staged construction will be used to allow use of the existing bridges during construction. Four Lanes of traffic (2-12’ Lanes in each direction) shall be maintained at all times during construction of the proposed bridge.

Minimize shoulder width reductions. On roadways with paved shoulders, maintain a minimum total width of paved shoulder area no less than 5 feet wide with a minimum 3-foot / 2-foot split between each paved shoulder; provide a minimum width of 2 feet of paved shoulder on one side of the travel way with a minimum width of 3 feet of paved shoulder on the other side of the travel way. On bridge structures, maintain a minimum total width of shoulder area no less than 4 feet wide with a 2-foot / 2-foot split between each shoulder; provide no less than 2 feet of shoulder width on each side of the travel way.

**EXHIBIT 4B – LOCATION SPECIFIC CRITERIA**

**Pavement Design**

New Construction (Mainline and Shoulders)

Surface – 110 psy OGFC & 200 psy HMA Surface Type A

Intermediate – 200 psy HMA Surface Type A

Base - 1600 psy HMA Base Type A

Alternate Base – 10 inch GAB plus 1050 psy HMA Base Type A

Existing Pavement

Overlay – 110 psy OGFC & 200 psy HMA Surface Type A

Surface Planing to remove existing OGFC prior to overlay

Temporary Pavement (median crossovers and existing shoulders used for temporary traffic)

Surface – 200 psy HMA Surface Type B

Intermediate – 200 psy HMA Surface Type B

Base – 1100 psy HMA Base Type A

**b) HYDROLOGY**

The proposed bridge will span over the Norfolk southern railroad and does not span any waterways.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 111'-3" (Includes 105'-6" Total Minimum Clear Roadway Width (52'-9" Minimum Clear Roadway Width North Bound Lane and 52'-9" Minimum Clear Roadway Width South Bound Lane), One – 2'-6" Median Barrier, Two -- 1'-6" Barrier Parapets, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers). Width provides for 6 lanes (3- 12' lanes in each direction), 4'- 9" inside shoulders, and 12' outside shoulders.

**Bridge Skew:** To be determined.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**EXHIBIT 4B – LOCATION SPECIFIC CRITERIA**

**General Bridge Layout Requirements**

The Contractor shall follow the bridge layout requirements as shown in Preliminary Bridge Layout sketch.

**Miscellaneous Requirements**

OGFC Requirements.

**Railroad Requirements:**

See Railroad Requirements in Special Provisions (Exhibit 5).

Specifications included in letter from Norfolk Southern dated 4-17-12 (Exhibit 8).

Final Roadway striping: 2-12' travel lanes will be striped in each direction with a minimum 12' (10' paved, 2' earth) outside shoulder width. The outside shoulder width may be wider to meet guardrail requirements. The remaining inside width will be striped as an inside shoulder.

Install impact attenuator on both approaches to median barrier. Contractor shall pave total median width for length of impact attenuator protecting the concrete median barrier. Impact attenuator shall be TL-3 and shall be in accordance with section 670 of the Standard Specifications for Highway Construction. Construct concrete foundation for impact attenuator in accordance to manufacturer's requirements. Install impact attenuator on both approaches to median barrier on bridge in accordance to manufacturer's recommendation. Grade approach area to attenuator in accordance with manufacturer's and SCDOT requirements.

SCDOT is responsible for temporary relocation of the existing Intelligent Transportation Systems (ITS) cable. SCDOT is also responsible for reattaching the ITS cable to the proposed bridge. The Contractor shall coordinate with SCDOT and include SCDOT's temporary relocation and reattachment in his coordination with the Railroad, including the railroad agreement.


**d) RIGHT OF WAY**

All right of way acquisitions for the I-85 bridge replacement shall be acquired and specified as controlled access.





EXHIBIT 4B – LOCATION SPECIFIC CRITERIA






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE K**

**ROUTE: S-46-103**

**CROSSING: FISHING CREEK**

**COUNTY: YORK**

**STRUCTURE NUMBER: 4670010300100**

a) **ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	2145 feet
<b>End of Existing Bridge:</b>	2460 feet
<b>Design Speed:</b>	50 mph
<b>Functional Classification:</b>	Rural Local Group 4
<b>Design ADT:</b>	1,400
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Miscellaneous**

Contractor shall secure fee simple right of way consistent with Department practices. Obtain uniform widths of right way along roadway to cover permanent improvements including ditches and slopes. Obtain area for bridge maintenance in accordance with HDM.

**Typical Section**

Roadway Approaches will consist of 2 – 11'-0" Lanes with 6'-0" Shoulders (2'-0" Paved Shoulders and 4'-0" Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on new alignment upstream of the existing structure. Traffic may be detoured during construction.

If traffic is detoured during construction, the CONTRACTOR shall detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

New Construction

- b. Surface – 150 psy HMA Surface Type D
- Intermediate – 200 psy HMA Intermediate Type C
- Base - 350 psy HMA Base Type B or 6 inches GAB

**EXHIBIT 4B – LOCATION SPECIFIC CRITERIA**

Existing Pavement

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching.

Overlay – 175 psy HMA Surface Type C

Variable milling for pavement tie-ins as directed by SCDOT

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

**c) STRUCTURE**

**Bridge Design Criteria**

**Superstructure Types Allowed:** Prestressed Concrete Girders  
Structural Steel Rolled W Beams  
Structural Steel Welded Plate Girders

**Minimum Outside Deck Width:**

If Prestressed Concrete Girders, Structural Steel Rolled W Beams, Structural Steel Welded Plate Girders, or Flat Slabs are used, then the minimum outside deck width shall be 37’-3” (Includes 34’-0” Clear Roadway Width, Two – 1’-6” Barrier Parapets, and Two – 1 ½” Slab Extensions for Slip Forming Barriers)

**Bridge Skew:** To be determined by hydraulic design.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**Seismic Design Criteria**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**General Bridge Layout Requirements**

The Contractor shall follow the minimum bridge length and span layout requirements as shown in Preliminary Bridge Layout sketch.

Note: Minimum bridge length shall be 400’-0” and minimum length of span over channel shall be 60’-0” as shown in the Preliminary Bridge Layout sketch.



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

BRIDGE PIN: FISHING CREEK  
REPLACE BRIDGE OVER FISHING CREEK






EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA




EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

**BRIDGE L**

**ROUTE: S-11-41**

**CROSSING: PEOPLES CREEK**

**COUNTY: CHEROKEE**

**STRUCTURE NUMBER: 1170004100100**

**a) ROADWAY**

<b>Minimum Approach Length*</b>	
<b>Beginning of Existing Bridge:</b>	200 feet
<b>End of Existing Bridge:</b>	200 feet
<b>Design Speed:</b>	35 mph
<b>Functional Classification:</b>	Urban Collector
<b>Design ADT:</b>	4200
<b>Terrain:</b>	Rolling

*\*Minimum Approach Length includes transition from project design criteria to existing condition.*

**Typical Section**

Roadway Approaches will consist of 2 – 12’-0” Lanes with 8’-0” Shoulders (2’-0” Paved Shoulders and 6’-0” Grassed Shoulders)

**Maintenance of Traffic**

The proposed bridge will be constructed on or near the existing horizontal alignment. Traffic will be detoured during construction.

The CONTRACTOR shall close structure and detour traffic using the detour route specified in this criteria while the new bridge is constructed.

**Pavement Design**

New Construction

- a. Surface –175 psy HMA Surface Type C
- b. Intermediate –200 psy HMA Intermediate Type C
- c. Base - 600 psy HMA Base Type B

Existing Pavement

8” of Full Depth Patching as directed by SCDOT in accordance with Special Provision – Section 401; Full Depth Asphalt Pavement Patching. Variable milling for pavement tie-ins as directed by SCDOT

**b) HYDROLOGY**

The project site is located in a FEMA Special Flood Hazard Area Zone AE based on latest maps reviewed by Department.

A no rise certification was obtained by SCDOT based on the bridge size/type included in the preliminary plan and profile drawings provided. If the contractor changes the design, the contractor will be responsible for all coordination and FEMA approvals.

**c) STRUCTURE**

**Bridge Design Criteria**

Superstructure Types Allowed:                      Prestressed Concrete Girders  
Cast-in-place concrete flat slab

**Minimum Outside Deck Width:**

The minimum outside deck width shall be 42'-7" (Includes 40'-0" Clear Roadway Width, Two -- 1'-2" concrete railing walls, and Two -- 1 ½" Slab Extensions for Slip Forming Barriers)

**Bridge Length:**

Minimum bridge length shall be 37'-0".

**Bridge Skew:**    20 degrees maximum, to be determined by hydraulic design.

**Seismic Design Criteria:**

Use SC Seismic Hazard Map Three-Point ADRS Curves provided in this criteria.

**Miscellaneous Requirements**

The use of MSE Walls as bridge abutments will not be allowed for this bridge.

**d) RIGHT OF WAY**

**Right of way:**

Right of way has been secured for the design as shown in the pdf plans signed by Anthony Fallaw and dated November 7, 2011

**e) DESIGN EXCEPTION**

A design exception is on file for the design of the right of way plans and may be used by the design team. The design exception is approved for a design speed of 25 mph for the horizontal curve on the northeast end of the new bridge structure.



EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

S-11-41 (Beech Street) over Peoples Creek  
Cherokee County








EXHIBIT 4B – LOCATION SPECIFIC CRITERIA

