



NOTES:

All exposed edges are to be chamfered 3/4".

All concrete shall be class "A".

Any removal of muck material below the bottom of the slabs considered necessary by the Engineer shall be measured in place and paid for at the unit price bid for common excavation. In addition the necessary back fill of the mucked volume will be measured in place before excavation and paid for at the unit price bid for common excavation.

Measurement for excavation for structures shall not extend below the bottoms of the slab foundation.

Drawn By: J. H. Hays 11-2-43

Traced By: J. H. Hays 11-2-43

Checked By: F. M. Joyce 11-2-43

Worked up By: W.B.B. 11-2-43; Revised By: W.B.B. 11-8-43

Checked By: A.T.C. 11-2-43; Checked By: A.T.C. 11-9-43

S.C. STATE HIGHWAY DEPARTMENT
COLUMBIA, S.C.

CONCRETE CULVERT
REINFORCED BOX TYPE
DOUBLE 10'x12'x36'-0"

STATION 327+58 PROJ. 40.290 RICHLAND CO.
SCALE 3/8" INCH = 1 FOOT DATE Nov. 2, 1943

CORRECT: _____

APPROVED: _____

BRIDGE ENGINEER

STATE HIGHWAY ENGINEER

CONCRETE * 154.51 CU. YDS.

STEEL 12,931 LBS.

EXCAVATION 2' 290 CU. YDS.

* Does not include concrete in Aprons

* Includes excavation for Aprons

