

Florence & Hutcheson
 501 Huger Street
 Columbia, SC 29201

Phone: (803)254-5800
 E-mail:

Fax: (803)929-0334

Operational Analysis

Analyst: JP
 Agency or Company: Florence & Hutcheson
 Date Performed: 9/23/2011
 Analysis Time Period: AM
 Freeway/Direction: I-385NB
 From/To: I-85SB to I-385NB (Ramp)
 Jurisdiction: Greenville, SC
 Analysis Year: 2015
 Description: I-85/I-385 Alternate 4A

Flow Inputs and Adjustments

| | | |
|-------------------------------|-------|---------|
| Volume, V | 1205 | veh/h |
| Peak-hour factor, PHF | 0.90 | |
| Peak 15-min volume, v15 | 335 | v |
| Trucks and buses | 18 | % |
| Recreational vehicles | 0 | % |
| Terrain type: | Level | |
| Grade | - | % |
| Segment length | - | mi |
| Trucks and buses PCE, ET | 1.5 | |
| Recreational vehicle PCE, ER | 1.2 | |
| Heavy vehicle adjustment, fHV | 0.917 | |
| Driver population factor, fp | 1.00 | |
| Flow rate, vp | 730 | pc/h/ln |

Speed Inputs and Adjustments

| | | |
|-----------------------------------|----------|----------|
| Lane width | - | ft |
| Right-side lateral clearance | - | ft |
| Total ramp density, TRD | - | ramps/mi |
| Number of lanes, N | 2 | |
| Free-flow speed: | Measured | |
| FFS or BFFS | 55.0 | mi/h |
| Lane width adjustment, fLW | - | mi/h |
| Lateral clearance adjustment, fLC | - | mi/h |
| TRD adjustment | - | mi/h |
| Free-flow speed, FFS | 55.0 | mi/h |

LOS and Performance Measures

| | | |
|--------------------------------|------|----------|
| Flow rate, vp | 730 | pc/h/ln |
| Free-flow speed, FFS | 55.0 | mi/h |
| Average passenger-car speed, S | 55.0 | mi/h |
| Number of lanes, N | 2 | |
| Density, D | 13.3 | pc/mi/ln |
| Level of service, LOS | B | |

Overall results are not computed when free-flow speed is less than 55 mph.