

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 8/25/2011
Analysis time period: AM
Freeway/Dir of Travel: I-385 SB
Junction: I-385 SB C-D - I-385SB
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 Alternate 4A

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	55.0	mph
Volume on freeway	2242	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	2	
Free-flow speed on ramp	45.0	mph
Volume on ramp	2084	vph
Length of first accel/decel lane	1150	ft
Length of second accel/decel lane	1500	ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	No	
Volume on adjacent Ramp		vph
Position of adjacent Ramp		
Type of adjacent Ramp		
Distance to adjacent Ramp		ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	2242	2084		vph
Peak-hour factor, PHF	0.90	0.90		
Peak 15-min volume, v15	623	579		v
Trucks and buses	18	18		%
Recreational vehicles	0	0		%
Terrain type:	Level	Level		
Grade	%	%		%
Length	mi	mi		mi
Trucks and buses PCE, ET	1.5	1.5		
Recreational vehicle PCE, ER	1.2	1.2		

Heavy vehicle adjustment, fHV	0.917	0.917	
Driver population factor, fP	1.00	1.00	
Flow rate, vp	2715	2524	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.555 \quad \text{Using Equation 0}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 1507 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	5239	6750	No
v ₃ or v _{av34}	1208 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1551		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	5239	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 12.3 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence B

Speed Estimation

Intermediate speed variable,	M _S = 0.209	
Space mean speed in ramp influence area,	S _R = 52.3	mph
Space mean speed in outer lanes,	S ₀ = 52.6	mph
Space mean speed for all vehicles,	S = 52.4	mph