

Florence & Hutcheson  
501 Huger Street  
Columbia, SC 29201

Phone: (803)254-5800  
E-mail:

Fax: (803)929-0334

### \_\_\_\_\_Merge Analysis\_\_\_\_\_

Analyst: JP  
Agency/Co.: Florence & Hutcheson  
Date performed: 8/25/2011  
Analysis time period: AM  
Freeway/Dir of Travel: I-385 SB  
Junction: Roper Mtn Rd  
Jurisdiction: Greenville, SC  
Analysis Year: 2035  
Description: I-85/I-385 Alternate 4A

### \_\_\_\_\_Freeway Data\_\_\_\_\_

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	55.0	mph
Volume on freeway	4238	vph

### \_\_\_\_\_On Ramp Data\_\_\_\_\_

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	55.0	mph
Volume on ramp	1359	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

### \_\_\_\_\_Adjacent Ramp Data (if one exists)\_\_\_\_\_

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2537	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	1780	ft

### \_\_\_\_\_Conversion to pc/h Under Base Conditions\_\_\_\_\_

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	4238	1359	2537	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1177	378	705	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	5133	1646	3073	pcph

# Estimation of V12 Merge Areas

L = 11377.27 Equation 13-6 or 13-7)

EQ

P = 1.000 Using Equation 3

FM

v = v (P ) = 5133 pc/h

12 F FM

# Capacity Checks

	Actual	Maximum	LOS F?
v	6779	6750	Yes
FO			
v or v	0 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	No	
3 av34			
Is v or v	> 1.5 v /2	No	
3 av34	12		
If yes, v	= 5133	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

# Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	6779	4600	Yes
R12			

# Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 48.2 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence F

# Speed Estimation

Intermediate speed variable,	M = 3.585	
	S	
Space mean speed in ramp influence area,	S = 8.4	mph
	R	
Space mean speed in outer lanes,	S = 55.0	mph
	0	
Space mean speed for all vehicles,	S = 8.4	mph