

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 8/24/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 Alternate 4A

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5930	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	2	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	2671	vph
Length of first accel/decel lane	350	ft
Length of second accel/decel lane	0	ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	2087	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	7300	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5930	2671	2087	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1647	742	580	v
Trucks and buses	18	15	15	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.930	0.930	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7182	3190	2493	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.260 \quad \text{Using Equation 0}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 4228 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	7182	9200	No
$v_{FO} = v_F - v_R$	3992	9200	No
v_R	3190	4200	No
v_3 or v_{av34}	1477 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4228$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4228	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 \frac{L}{D}$	$= 34.3$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.585$	
Space mean speed in ramp influence area,	$S_R = 49.5$	mph
Space mean speed in outer lanes,	$S_0 = 64.0$	mph
Space mean speed for all vehicles,	$S = 54.6$	mph