

Florence & Hutcheson  
501 Huger Street  
Columbia, SC 29201

Phone: (803)254-5800  
E-mail:

Fax: (803)929-0334

### \_\_\_\_\_Merge Analysis\_\_\_\_\_

Analyst: JP  
Agency/Co.: Florence & Hutcheson  
Date performed: 8/9/2011  
Analysis time period: AM  
Freeway/Dir of Travel: I-85 SB  
Junction: Pelham Rd  
Jurisdiction: Greenville, SC  
Analysis Year: 2035  
Description: I-85/I-385 Alternate 4A

### \_\_\_\_\_Freeway Data\_\_\_\_\_

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6467	vph

### \_\_\_\_\_On Ramp Data\_\_\_\_\_

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	443	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

### \_\_\_\_\_Adjacent Ramp Data (if one exists)\_\_\_\_\_

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2783	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	2800	ft

### \_\_\_\_\_Conversion to pc/h Under Base Conditions\_\_\_\_\_

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6467	443	2783	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1796	123	773	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7832	537	3371	pcph

#### Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = 0.151 Using Equation 4

FM

v = v (P ) = 1180 pc/h

12 F FM

#### Capacity Checks

		Actual	Maximum	LOS F?
v		8369	9200	No
FO				
v or v		3326 pc/h	(Equation 13-14 or 13-17)	
3	av34			
Is v or v	> 2700 pc/h?	Yes		
3	av34			
Is v or v	> 1.5 v /2	Yes		
3	av34 12			
If yes, v	= 3132	(Equation 13-15, 13-16, 13-18, or 13-19)		
12A				

#### Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	8369	4600	No
12A			

#### Level of Service Determination (if not F)

Density, D =  $5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A$  = 30.4 pc/mi/ln

Level of service for ramp-freeway junction areas of influence D

#### Speed Estimation

Intermediate speed variable,	M = 0.441	
	S	
Space mean speed in ramp influence area,	S = 52.1	mph
	R	
Space mean speed in outer lanes,	S = 53.2	mph
	0	
Space mean speed for all vehicles,	S = 52.7	mph