

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: NJ
Agency/Co.: Florence & Hutcheson
Date performed: 3/24/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 WB OFF-RAMP
Jurisdiction: Greenville, SC
Analysis Year: 2010
Description: I-85/I-385 Existing

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	3	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3527	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	355	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	407	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	420	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	3527		355		407	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	980		99		113	v
Trucks and buses	18		15		15	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.930	0.930	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4272	424	486	pcph

Estimation of V12 Diverge Areas

$$L = 3546.62 \text{ (Equation 13-12 or 13-13)}$$

EQ

$$P = 1.000 \text{ Using Equation 6}$$

FD

$$v_{12} = v_R + (v_F - v_R) P = 4272 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	4272	6900	No
$v_{FO} = v_F - v_R$	3848	6900	No
v_R	424	1900	No
$v_3 \text{ or } v_{av34}$	0 pc/h	(Equation 13-14 or 13-17)	
Is $v_3 \text{ or } v_{av34} > 2700 \text{ pc/h?}$		No	
Is $v_3 \text{ or } v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4272$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4272	4400	No

Level of Service Determination (if not F)

Density, $D = 4.252 + 0.0086 v_R - 0.009 L_D = 37.2 \text{ pc/mi/ln}$

Level of service for ramp-freeway junction areas of influence E

Speed Estimation

Intermediate speed variable,	$D_S = 0.596$	
Space mean speed in ramp influence area,	$S_R = 49.3$	mph
Space mean speed in outer lanes,	$S_0 = 65.8$	mph
Space mean speed for all vehicles,	$S = 49.3$	mph