

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-385 NB
Junction: Woodruff
Jurisdiction: Greenville, SC
Analysis Year: 2015
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	55.0	mph
Volume on freeway	4268	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1131	vph
Length of first accel/decel lane	1100	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1214	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	1240	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	4268	1131	1214	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1186	314	337	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	5169	1370	1470	pcph

Estimation of V12 Merge Areas

$$L = 6467.22 \text{ (Equation 13-6 or 13-7)}$$

EQ

$$P = 0.860 \text{ Using Equation 3}$$

FM

$$v_{12} = v_F(P) = 4447 \text{ pc/h}$$

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	6539	6750	No
v ₃ or v _{av34}	722 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		No	
If yes, v _{12A} = 4447		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{R12}	6539	4600	Yes

Level of Service Determination (if not F)

Density, $D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 43.3 \text{ pc/mi/ln}$

Level of service for ramp-freeway junction areas of influence E

Speed Estimation

Intermediate speed variable,	M	= 1.532	
Space mean speed in ramp influence area,	S _R	= 35.1	mph
Space mean speed in outer lanes,	S ₀	= 54.2	mph
Space mean speed for all vehicles,	S	= 36.5	mph