

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 (EXIT48A)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6412	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	30.0	mph
Volume on ramp	354	vph
Length of first accel/decel lane	700	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	330	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6412	354	330	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1781	98	92	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7766	429	400	pcph

Estimation of V12 Diverge Areas

L = (Equation 13-12 or 13-13)

EQ

P = 0.436 Using Equation 8

FD

$v_{12} = v_R + (v_F - v_R) P = 3628 \text{ pc/h}$

Capacity Checks

	Actual	Maximum	LOS F?
$v_F = v_{Fi}$	7766	9200	No
$v_F = v_F - v_R$	7337	9200	No
v_R	429	2000	No
v_3 or v_{av34}	2069 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700 \text{ pc/h?}$		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3628$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	3628	4400	No

Level of Service Determination (if not F)

Density, $D = 4.252 + 0.0086 v_{12} - 0.009 L_D = 29.2 \text{ pc/mi/ln}$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	$D_S = 0.532$	
Space mean speed in ramp influence area,	$S_R = 50.4$	mph
Space mean speed in outer lanes,	$S_0 = 61.7$	mph
Space mean speed for all vehicles,	$S = 55.8$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6058	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	330	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	825	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	420	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6058	330	825	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1683	92	229	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7337	400	999	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.168 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 1231 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7737	9200	No
v ₃ or v _{av34}	3053 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2934		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7737	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 28.7 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.409	
Space mean speed in ramp influence area,	S _R = 52.6	mph
Space mean speed in outer lanes,	S ₀ = 53.9	mph
Space mean speed for all vehicles,	S = 53.3	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6058	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	330	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	354	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	500	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6058	330	354	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1683	92	98	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7337	400	429	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.168 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 1231 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7737	9200	No
v ₃ or v _{av34}	3053 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2934		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7737	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 28.7 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.409	
Space mean speed in ramp influence area,	S _R = 52.6	mph
Space mean speed in outer lanes,	S ₀ = 53.9	mph
Space mean speed for all vehicles,	S = 53.3	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6388	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	825	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	787	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	450	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6388	825	787	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1774	229	219	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7737	999	953	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 3937 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	7737	9200	No
$v_{FO} = v_F - v_R$	6738	9200	No
v_R	999	1900	No
v_3 or v_{av34}	1900 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3937$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	3937	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 34.3$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.648$	
Space mean speed in ramp influence area,	$S_R = 48.3$	mph
Space mean speed in outer lanes,	$S_0 = 62.3$	mph
Space mean speed for all vehicles,	$S = 54.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6388	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	825	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	330	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	420	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	6388		825		330	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	1774		229		92	v
Trucks and buses	18		18		18	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7737	999	400	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P = 3937 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	7737	9200	No
$v_{FO} = v_F - v_R$	6738	9200	No
v_R	999	1900	No
v_3 or v_{av34}	1900 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3937$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	3937	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 34.3$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.648$	
Space mean speed in ramp influence area,	$S_R = 48.3$	mph
Space mean speed in outer lanes,	$S_0 = 62.3$	mph
Space mean speed for all vehicles,	$S = 54.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5563	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	787	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	825	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	450	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5563	787	825	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1545	219	229	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6737	953	999	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.099 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 665 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7690	9200	No
v ₃ or v _{av34}	3036 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2694		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7690	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 30.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.438	
Space mean speed in ramp influence area,	S _R = 52.1	mph
Space mean speed in outer lanes,	S ₀ = 54.5	mph
Space mean speed for all vehicles,	S = 53.4	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6840	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	30.0	mph
Volume on ramp	668	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	1491	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6840	668	1491	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1900	186	414	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8284	809	1806	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 4068 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	8284	9200	No
$v_{FO} = v_F - v_R$	7475	9200	No
v_R	809	2000	No
v_3 or v_{av34}	2108 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4068$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4068	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 33.4$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.566$	
Space mean speed in ramp influence area,	$S_R = 49.8$	mph
Space mean speed in outer lanes,	$S_0 = 61.5$	mph
Space mean speed for all vehicles,	$S = 55.1$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6172	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	1491	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1065	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	420	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6172	1491	1065	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1714	414	296	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7475	1806	1290	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = -0.008 Using Equation 4

FM

v = v (P) = -58 pc/h

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v	9281	9200	Yes
FO			
v or v	3766 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	Yes	
3 av34			
Is v or v	> 1.5 v /2	Yes	
3 av34 12			
If yes, v	= 2990	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	9281	4600	Yes
12A			

Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 39.4 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M = 0.772	
	S	
Space mean speed in ramp influence area,	S = 46.1	mph
	R	
Space mean speed in outer lanes,	S = 53.7	mph
	0	
Space mean speed for all vehicles,	S = 49.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6172	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	1491	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	668	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	500	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6172	1491	668	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1714	414	186	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7475	1806	809	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.008 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -58 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	9281	9200	Yes
v ₃ or v _{av34}	3766 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2990		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	9281	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 39.4 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M _S = 0.772	
Space mean speed in ramp influence area,	S _R = 46.1	mph
Space mean speed in outer lanes,	S ₀ = 53.7	mph
Space mean speed for all vehicles,	S = 49.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Diverge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT 48A)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7663	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	1065	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	615	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	468	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7663	1065	615	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2129	296	171	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9281	1290	745	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P = 4774 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
$v_{Fi} = v_F$		9281	9200	Yes
$v_{FO} = v_F - v_R$		7991	9200	No
v_R		1290	1900	No
v_3 or v_{av34}		2253 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?			No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$			No	
If yes, $v_{12A} = 4774$			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4774	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$				
					41.5 pc/mi/ln
Level of service for ramp-freeway junction areas of influence F					

Speed Estimation

Intermediate speed variable,	$D = 0.674$	
Space mean speed in ramp influence area,	$S_R = 47.9$	mph
Space mean speed in outer lanes,	$S_0 = 60.9$	mph
Space mean speed for all vehicles,	$S = 53.4$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT 48A)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7663	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	1065	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	1491	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	420	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7663	1065	1491	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2129	296	414	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9281	1290	1806	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P = 4774 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
$v_{Fi} = v_F$		9281	9200	Yes
$v_{FO} = v_F - v_R$		7991	9200	No
v_R		1290	1900	No
v_3 or v_{av34}		2253 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?			No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$			No	
If yes, $v_{12A} = 4774$			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4774	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$			
Level of service for ramp-freeway junction areas of influence F				

Speed Estimation

Intermediate speed variable,	$D = 0.674$		
Space mean speed in ramp influence area,	$S_R = 47.9$	mph	
Space mean speed in outer lanes,	$S_0 = 60.9$	mph	
Space mean speed for all vehicles,	$S = 53.4$	mph	

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6598	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	615	vph
Length of first accel/decel lane	500	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1065	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	470	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6598	615	1065	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1833	171	296	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7991	745	1290	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.125 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 996 \quad \text{pc/h}$$

-----Capacity Checks-----

		Actual	Maximum	LOS F?
v _{FO}		8736	9200	No
v ₃ or v _{av34}		3497 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34}	> 2700 pc/h?		Yes	
Is v ₃ or v _{av34}	> 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A}	= 3196		(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	8736	4600	No

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 32.7 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

-----Speed Estimation-----

Intermediate speed variable,	M _S	= 0.497	
Space mean speed in ramp influence area,	S _R	= 51.1	mph
Space mean speed in outer lanes,	S ₀	= 52.9	mph
Space mean speed for all vehicles,	S	= 52.0	mph

Florence & Hutcheson
 501 Huger Street
 Columbia, SC 29201

Phone: (803)254-5800
 E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
 Agency/Co.: Florence & Hutcheson
 Date performed: 4/5/2011
 Analysis time period: PM
 Freeway/Dir of Travel: I-85 NB
 Junction: US 276 (EXIT48A)
 Jurisdiction: Greenville, SC
 Analysis Year: 2035
 Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6609	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	30.0	mph
Volume on ramp	1676	vph
Length of first accel/decel lane	700	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	617	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6609	1676	617	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1836	466	171	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8004	2030	747	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 4635 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	8004	9200	No
$v_{FO} = v_F - v_R$	5974	9200	No
v_R	2030	2000	Yes
v_3 or v_{av34}	1684 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4635$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4635	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 37.8$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.676$	
Space mean speed in ramp influence area,	$S_R = 47.8$	mph
Space mean speed in outer lanes,	$S_0 = 63.2$	mph
Space mean speed for all vehicles,	$S = 53.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	4933	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	617	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	506	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	420	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	4933	617	506	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1370	171	141	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	5974	747	613	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.124 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 743 \quad \text{pc/h}$$

-----Capacity Checks-----

	Actual	Maximum	LOS F?
v _{FO}	6721	9200	No
v ₃ or v _{av34}	2615 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2389		(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	6721	4600	No

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 27.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

-----Speed Estimation-----

Intermediate speed variable,	M _S = 0.390	
Space mean speed in ramp influence area,	S _R = 53.0	mph
Space mean speed in outer lanes,	S ₀ = 55.3	mph
Space mean speed for all vehicles,	S = 54.2	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	4933	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	617	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1676	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	500	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	4933	617	1676	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1370	171	466	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	5974	747	2030	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.124 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 743 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	6721	9200	No
v ₃ or v _{av34}	2615 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2389		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	6721	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 27.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	M _S = 0.390	
Space mean speed in ramp influence area,	S _R = 53.0	mph
Space mean speed in outer lanes,	S ₀ = 55.3	mph
Space mean speed for all vehicles,	S = 54.2	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5550	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	506	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	886	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	450	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5550	506	886	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1542	141	246	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6722	613	1073	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 3277 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	6722	9200	No
$v_{FO} = v_F - v_R$	6109	9200	No
v_R	613	1900	No
v_3 or v_{av34}	1722 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3277$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	3277	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 28.7$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.613$	
Space mean speed in ramp influence area,	$S_R = 49.0$	mph
Space mean speed in outer lanes,	$S_0 = 63.0$	mph
Space mean speed for all vehicles,	$S = 55.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5550	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	506	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	617	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	420	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5550	506	617	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1542	141	171	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6722	613	747	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 3277 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	6722	9200	No
$v_{FO} = v_F - v_R$	6109	9200	No
v_R	613	1900	No
v_3 or v_{av34}	1722 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3277$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	3277	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 28.7$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence D			

Speed Estimation

Intermediate speed variable,	$D_S = 0.613$	
Space mean speed in ramp influence area,	$S_R = 49.0$	mph
Space mean speed in outer lanes,	$S_0 = 63.0$	mph
Space mean speed for all vehicles,	$S = 55.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5044	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	886	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	506	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	450	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5044	886	506	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1401	246	141	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6109	1073	613	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.084 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 511 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7182	9200	No
v ₃ or v _{av34}	2799 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2443		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7182	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 29.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.419	
Space mean speed in ramp influence area,	S _R = 52.5	mph
Space mean speed in outer lanes,	S ₀ = 55.2	mph
Space mean speed for all vehicles,	S = 53.8	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT48B)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8610	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	30.0	mph
Volume on ramp	604	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	891	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	8610	604	891	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2392	168	248	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	10428	732	1079	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 4959 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	10428	9200	Yes
$v_{FO} = v_F - v_R$	9696	9200	Yes
v_R	732	2000	No
v_3 or v_{av34}	2734 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 5028$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	5028	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 41.6$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.559$	
Space mean speed in ramp influence area,	$S_R = 49.9$	mph
Space mean speed in outer lanes,	$S_0 = 59.2$	mph
Space mean speed for all vehicles,	$S = 54.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8006	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	891	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	714	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	420	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	8006	891	714	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2224	248	198	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9696	1079	865	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.083 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 804 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	10775	9200	Yes
v ₃ or v _{av34}	4446 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 3878		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	10775	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 41.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M _S = 0.854	
Space mean speed in ramp influence area,	S _R = 44.6	mph
Space mean speed in outer lanes,	S ₀ = 49.8	mph
Space mean speed for all vehicles,	S = 47.3	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8006	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	891	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	604	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	500	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	8006	891	604	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2224	248	168	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9696	1079	732	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.083 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 804 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	10775	9200	Yes
v_3 or v_{av34}	4446 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 3878$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	10775	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 41.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	$M_S = 0.854$	
Space mean speed in ramp influence area,	$S_R = 44.6$	mph
Space mean speed in outer lanes,	$S_0 = 49.8$	mph
Space mean speed for all vehicles,	$S = 47.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT 48A)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8897	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	714	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	826	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	468	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	8897		714		826	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	2471		198		229	v
Trucks and buses	18		18		18	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	10775	865	1000	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 5186 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	10775	9200	Yes
$v_{FO} = v_F - v_R$	9910	9200	Yes
v_R	865	1900	No
v_3 or v_{av34}	2794 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 5375$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	5375	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 46.7$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.636$	
Space mean speed in ramp influence area,	$S_R = 48.6$	mph
Space mean speed in outer lanes,	$S_0 = 59.2$	mph
Space mean speed for all vehicles,	$S = 53.4$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276 (EXIT 48A)
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8897	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	25.0	mph
Volume on ramp	714	vph
Length of first accel/decel lane	420	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	891	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	420	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	8897		714		891	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	2471		198		248	v
Trucks and buses	18		18		18	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	10775	865	1079	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 5186 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
$v_{Fi} = v_F$		10775	9200	Yes
$v_{FO} = v_F - v_R$		9910	9200	Yes
v_R		865	1900	No
v_3 or v_{av34}		2794 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?			Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$			No	
If yes, $v_{12A} = 5375$			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	5375	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$				
					46.7 pc/mi/ln
Level of service for ramp-freeway junction areas of influence F					

Speed Estimation

Intermediate speed variable,	$D_S = 0.636$	
Space mean speed in ramp influence area,	$S_R = 48.6$	mph
Space mean speed in outer lanes,	$S_0 = 59.2$	mph
Space mean speed for all vehicles,	$S = 53.4$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: US 276
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8183	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	25.0	mph
Volume on ramp	826	vph
Length of first accel/decel lane	500	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	714	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	470	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	8183	826	714	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2273	229	198	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9911	1000	865	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.093 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 920 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	10911	9200	Yes
v_3 or v_{av34}	4495 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 3964$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	10911	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 40.6 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	$M_S = 0.854$	
Space mean speed in ramp influence area,	$S_R = 44.6$	mph
Space mean speed in outer lanes,	$S_0 = 49.4$	mph
Space mean speed for all vehicles,	$S = 47.1$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: Woodruff Rd.
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6004	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	836	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2055	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2250	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6004	836	2055	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1668	232	571	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7272	1012	2489	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.091 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 664 \quad \text{pc/h}$$

-----Capacity Checks-----

		Actual	Maximum	LOS F?
v _{FO}		8284	9200	No
v ₃ or v _{av34}		3304 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?			Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2			Yes	
If yes, v _{12A} = 2908			(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	8284	4600	No

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 26.2 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

-----Speed Estimation-----

Intermediate speed variable,	M _S = 0.383	
Space mean speed in ramp influence area,	S _R = 53.1	mph
Space mean speed in outer lanes,	S ₀ = 53.9	mph
Space mean speed for all vehicles,	S = 53.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: Woodruff Rd.
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7192	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1418	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1992	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2250	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7192	1418	1992	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1998	394	553	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8710	1717	2413	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = 0.003 Using Equation 4

FM

v = v (P) = 28 pc/h

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v	10427	9200	Yes
FO			
v or v	4341 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	Yes	
3 av34			
Is v or v	> 1.5 v /2	Yes	
3 av34	12		
If yes, v	= 3484	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	10427	4600	Yes
12A			

Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 35.8 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M = 0.894	
	S	
Space mean speed in ramp influence area,	S = 43.9	mph
	R	
Space mean speed in outer lanes,	S = 51.6	mph
	0	
Space mean speed for all vehicles,	S = 47.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6350	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	2607	vph
Length of first accel/decel lane	350	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	641	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	4500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6350	2607	641	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1764	724	178	v
Trucks and buses	18	15	15	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.930	0.930	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7691	3114	766	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 5110 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	7691	9200	No
$v_{FO} = v_F - v_R$	4577	9200	No
v_R	3114	2100	Yes
v_3 or v_{av34}	1290 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 5110$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	5110	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 45.0$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.578$	
Space mean speed in ramp influence area,	$S_R = 49.6$	mph
Space mean speed in outer lanes,	$S_0 = 64.7$	mph
Space mean speed for all vehicles,	$S = 53.8$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3743	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	641	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	3480	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	1060	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3743	641	3480	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1040	178	967	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4533	776	4215	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.121 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 548 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	5309	9200	No
v ₃ or v _{av34}	1992 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1813		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	5309	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 21.2 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	M _S = 0.314	
Space mean speed in ramp influence area,	S _R = 54.3	mph
Space mean speed in outer lanes,	S ₀ = 56.9	mph
Space mean speed for all vehicles,	S = 55.6	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3743	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	641	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2607	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	4500	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3743	641	2607	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1040	178	724	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4533	776	3157	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.121 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 548 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	5309	9200	No
v ₃ or v _{av34}	1992 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1813		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	5309	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 21.2 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	M _S = 0.314	
Space mean speed in ramp influence area,	S _R = 54.3	mph
Space mean speed in outer lanes,	S ₀ = 56.9	mph
Space mean speed for all vehicles,	S = 55.6	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8859	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	4910	vph
Length of first accel/decel lane	600	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	2055	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	5100	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	8859		4910		2055	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	2461		1364		571	v
Trucks and buses	18		18		18	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	10729	5947	2489	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 8032 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
$v_{Fi} = v_F$		10729	9200	Yes
$v_{FO} = v_F - v_R$		4782	9200	No
v_R		5947	2100	Yes
v_3 or v_{av34}		1348 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?			No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$			No	
If yes, $v_{12A} = 8032$			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	8032	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 67.9$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.833$	
Space mean speed in ramp influence area,	$S_R = 45.0$	mph
Space mean speed in outer lanes,	$S_0 = 64.5$	mph
Space mean speed for all vehicles,	$S = 48.7$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3949	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	2055	vph
Length of first accel/decel lane	900	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	836	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2250	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3949	2055	836	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1097	571	232	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4783	2489	1012	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.093 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -445 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7272	9200	No
v ₃ or v _{av34}	2614 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1913		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7272	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 33.0 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.558	
Space mean speed in ramp influence area,	S _R = 50.0	mph
Space mean speed in outer lanes,	S ₀ = 56.6	mph
Space mean speed for all vehicles,	S = 52.4	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3949	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	2055	vph
Length of first accel/decel lane	900	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	4910	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	5100	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3949	2055	4910	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1097	571	1364	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4783	2489	5947	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.093 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -445 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7272	9200	No
v ₃ or v _{av34}	2614 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1913		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7272	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 33.0 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.558	
Space mean speed in ramp influence area,	S _R = 50.0	mph
Space mean speed in outer lanes,	S ₀ = 56.6	mph
Space mean speed for all vehicles,	S = 52.4	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5930	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	2671	vph
Length of first accel/decel lane	350	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	2087	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	4500	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5930	2671	2087	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1647	742	580	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7182	3235	2528	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P = 4956 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	7182	9200	No
$v_{FO} = v_F - v_R$	3947	9200	No
v_R	3235	2100	Yes
v_3 or v_{av34}	1113 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4956$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4956	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 43.7$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.589$	
Space mean speed in ramp influence area,	$S_R = 49.4$	mph
Space mean speed in outer lanes,	$S_0 = 65.4$	mph
Space mean speed for all vehicles,	$S = 53.4$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3259	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	2087	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	4388	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	1060	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3259	2087	4388	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	905	580	1219	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	3947	2528	5314	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.098 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -387 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	6475	9200	No
v ₃ or v _{av34}	2167 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 1578		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	6475	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 32.3 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.499	
Space mean speed in ramp influence area,	S _R = 51.0	mph
Space mean speed in outer lanes,	S ₀ = 57.5	mph
Space mean speed for all vehicles,	S = 53.2	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	3259	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	2087	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2671	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	4500	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3259	2087	2671	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	905	580	742	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	3947	2528	3235	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = -0.098 Using Equation 4

FM

v = v (P) = -387 pc/h

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v	6475	9200	No
FO			
v or v	2167 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	No	
3 av34			
Is v or v	> 1.5 v /2	Yes	
3 av34	12		
If yes, v	= 1578	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	6475	4600	No
12A			

Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 32.3 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M = 0.499	
	S	
Space mean speed in ramp influence area,	S = 51.0	mph
	R	
Space mean speed in outer lanes,	S = 57.5	mph
	0	
Space mean speed for all vehicles,	S = 53.2	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	9099	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	3899	vph
Length of first accel/decel lane	600	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	1992	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	5100	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway		Ramp		Adjacent Ramp	
Volume, V (vph)	9099		3899		1992	vph
Peak-hour factor, PHF	0.90		0.90		0.90	
Peak 15-min volume, v15	2528		1083		553	v
Trucks and buses	18		18		18	%
Recreational vehicles	0		0		0	%
Terrain type:	Level		Level		Level	
Grade	0.00	%	0.00	%	0.00	%
Length	0.00	mi	0.00	mi	0.00	mi
Trucks and buses PCE, ET	1.5		1.5		1.5	
Recreational vehicle PCE, ER	1.2		1.2		1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	11020	4722	2413	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 7468 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	11020	9200	Yes
$v_{FO} = v_F - v_R$	6298	9200	No
v_R	4722	2100	Yes
v_3 or v_{av34}	1776 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 7468$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	7468	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 63.1$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.723$	
Space mean speed in ramp influence area,	$S_R = 47.0$	mph
Space mean speed in outer lanes,	$S_0 = 62.8$	mph
Space mean speed for all vehicles,	$S = 51.1$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5200	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1992	vph
Length of first accel/decel lane	900	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1418	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2250	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5200	1992	1418	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1444	553	394	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6298	2413	1717	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.084 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -527 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	8711	9200	No
v ₃ or v _{av34}	3412 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2519		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	8711	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 37.2 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence E

Speed Estimation

Intermediate speed variable,	M _S = 0.781	
Space mean speed in ramp influence area,	S _R = 45.9	mph
Space mean speed in outer lanes,	S ₀ = 55.0	mph
Space mean speed for all vehicles,	S = 49.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: C-D ROAD
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5200	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1992	vph
Length of first accel/decel lane	900	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	3899	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	5100	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5200	1992	3899	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1444	553	1083	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6298	2413	4722	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.084 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -527 \text{ pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	8711	9200	No
v ₃ or v _{av34}	3412 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2519		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	8711	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 37.2 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence E

Speed Estimation

Intermediate speed variable,	M _S = 0.781	
Space mean speed in ramp influence area,	S _R = 45.9	mph
Space mean speed in outer lanes,	S ₀ = 55.0	mph
Space mean speed for all vehicles,	S = 49.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: I385
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	4384	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	55.0	mph
Volume on ramp	3480	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	641	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	1060	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	4384	3480	641	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1218	967	178	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	5310	4215	776	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = -0.309 Using Equation 4

FM

$v_{12} = v_F (P_{FM}) = -1640 \text{ pc/h}$

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	9525	9200	Yes
v_3 or v_{av34}	3475 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700 \text{ pc/h?}$		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 2124$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	9525	4600	Yes

Level of Service Determination (if not F)

Density, $D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 43.6 \text{ pc/mi/ln}$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M = 2.364	
Space mean speed in ramp influence area,	$S_R = 17.4$	mph
Space mean speed in outer lanes,	$S_0 = 56.1$	mph
Space mean speed for all vehicles,	$S = 22.7$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: I385
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5346	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	55.0	mph
Volume on ramp	4388	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2087	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	1060	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5346	4388	2087	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1485	1219	580	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6475	5314	2528	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = -0.446 Using Equation 4

FM

v = v (P) = -2890 pc/h

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v	11789	9200	Yes
FO			
v or v	4682 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	Yes	
3 av34			
Is v or v	> 1.5 v /2	Yes	
3 av34	12		
If yes, v	= 2590	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	11789	4600	Yes
12A			

Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 55.3 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M = 10.718
	S
Space mean speed in ramp influence area,	S = -132.9 mph
	R
Space mean speed in outer lanes,	S = 54.8 mph
	0
Space mean speed for all vehicles,	S = 1032.6 mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Diverge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Road
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7864	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	2460	vph
Length of first accel/decel lane	625	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	1131	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	1325	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7864	2460	1131	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2184	683	314	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9524	2979	1370	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 5833 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
$v_{Fi} = v_F$		9524	9200	Yes
$v_{FO} = v_F - v_R$		6545	9200	No
v_R		2979	2000	Yes
v_3 or v_{av34}		1845 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?			No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$			No	
If yes, $v_{12A} = 5833$			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	5833	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 48.8$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.696$	
Space mean speed in ramp influence area,	$S_R = 47.5$	mph
Space mean speed in outer lanes,	$S_0 = 62.5$	mph
Space mean speed for all vehicles,	$S = 52.4$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5404	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	1131	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	857	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2900	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5404	1131	857	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1501	314	238	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6545	1370	1038	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.047 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 305 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7915	9200	No
v ₃ or v _{av34}	3120 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2618		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7915	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 31.9 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.492	
Space mean speed in ramp influence area,	S _R = 51.1	mph
Space mean speed in outer lanes,	S ₀ = 54.7	mph
Space mean speed for all vehicles,	S = 52.9	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	5404	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	1131	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2460	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	1300	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	5404	1131	2460	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1501	314	683	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	6545	1370	2979	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.047 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 305 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	7915	9200	No
v ₃ or v _{av34}	3120 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 2618		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	7915	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 31.9 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	M _S = 0.492	
Space mean speed in ramp influence area,	S _R = 51.1	mph
Space mean speed in outer lanes,	S ₀ = 54.7	mph
Space mean speed for all vehicles,	S = 52.9	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6535	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	857	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1131	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2800	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6535	857	1131	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1815	238	314	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7915	1038	1370	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.088 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 697 \quad \text{pc/h}$$

-----Capacity Checks-----

		Actual	Maximum	LOS F?
v _{FO}		8953	9200	No
v ₃ or v _{av34}		3609 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?			Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2			Yes	
If yes, v _{12A} = 3166			(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	8953	4600	No

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 28.4 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

-----Speed Estimation-----

Intermediate speed variable,	M _S = 0.447	
Space mean speed in ramp influence area,	S _R = 52.0	mph
Space mean speed in outer lanes,	S ₀ = 53.0	mph
Space mean speed for all vehicles,	S = 52.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Road
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	9250	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	2783	vph
Length of first accel/decel lane	1400	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	443	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2000	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	9250	2783	443	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2569	773	123	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	11203	3371	537	pcph

Estimation of V12 Diverge Areas

L = (Equation 13-12 or 13-13)

EQ

P = 0.436 Using Equation 8

FD

$v_{12} = v_R + (v_F - v_R) P_{FD} = 6786 \text{ pc/h}$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	11203	9200	Yes
$v_{FO} = v_F - v_R$	7832	9200	No
v_R	3371	2100	Yes
v_3 or v_{av34}	2208 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700 \text{ pc/h?}$		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 6786$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	6786	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 \frac{L}{D}$	= 50.0	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.601$	
Space mean speed in ramp influence area,	$S_R = 49.2$	mph
Space mean speed in outer lanes,	$S_0 = 61.1$	mph
Space mean speed for all vehicles,	$S = 53.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 6/24/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6467	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	443	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1949	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2760	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6467	443	1949	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1796	123	541	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7832	537	2360	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.593 \quad \text{Using Equation 1}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 4644 \quad \text{pc/h}$$

-----Capacity Checks-----

		Actual	Maximum	LOS F?
v _{FO}		8369	6900	Yes
v ₃ or v _{av34}		3188 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?			Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2			No	
If yes, v _{12A} = 5132			(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	8369	4600	Yes

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 46.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

-----Speed Estimation-----

Intermediate speed variable,	M _S = 1.418	
Space mean speed in ramp influence area,	S _R = 34.5	mph
Space mean speed in outer lanes,	S ₀ = 51.1	mph
Space mean speed for all vehicles,	S = 38.5	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800

Fax: (803)929-0334

E-mail:

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6467	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	443	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2783	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	2800	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6467	443	2783	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1796	123	773	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	7832	537	3371	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.151 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 1180 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	8369	9200	No
v_3 or v_{av34}	3326 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 3132$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	8369	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 30.4 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	$M_S = 0.441$	
Space mean speed in ramp influence area,	$S_R = 52.1$	mph
Space mean speed in outer lanes,	$S_0 = 53.2$	mph
Space mean speed for all vehicles,	$S = 52.7$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: AM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6910	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1949	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	443	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2800	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6910	1949	443	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1919	541	123	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8369	2360	537	pcph

Estimation of V12 Merge Areas

L = (Equation 13-6 or 13-7)

EQ

P = -0.077 Using Equation 4

FM

v = v (P) = -645 pc/h

12 F FM

Capacity Checks

	Actual	Maximum	LOS F?
v	10729	9200	Yes
FO			
v or v	4507 pc/h	(Equation 13-14 or 13-17)	
3 av34			
Is v or v	> 2700 pc/h?	Yes	
3 av34			
Is v or v	> 1.5 v /2	Yes	
3 av34	12		
If yes, v	= 3347	(Equation 13-15, 13-16, 13-18, or 13-19)	
12A			

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v	10729	4600	Yes
12A			

Level of Service Determination (if not F)

Density, D = 5.475 + 0.00734 v + 0.0078 v - 0.00627 L = 39.5 pc/mi/ln

R R 12 A

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M = 1.360	
	S	
Space mean speed in ramp influence area,	S = 35.5	mph
	R	
Space mean speed in outer lanes,	S = 52.2	mph
	0	
Space mean speed for all vehicles,	S = 41.8	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Road
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	9734	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	2774	vph
Length of first accel/decel lane	625	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	1381	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	1325	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	9734	2774	1381	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2704	771	384	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	11789	3360	1673	pcph

Estimation of V12 Diverge Areas

L = (Equation 13-12 or 13-13)

EQ

P = 0.436 Using Equation 8

FD

$v_{12} = v_R + (v_F - v_R) P_{FD} = 7035 \text{ pc/h}$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	11789	9200	Yes
$v_{FO} = v_F - v_R$	8429	9200	No
v_R	3360	2000	Yes
v_3 or v_{av34}	2377 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700 \text{ pc/h?}$		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 7035$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	7035	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	= 59.1	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.730$	
Space mean speed in ramp influence area,	$S_R = 46.9$	mph
Space mean speed in outer lanes,	$S_0 = 60.4$	mph
Space mean speed for all vehicles,	$S = 51.5$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6960	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	1381	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1127	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2900	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6960	1381	1127	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1933	384	313	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8429	1673	1365	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.009 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 73 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	10102	9200	Yes
v_3 or v_{av34}	4178 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 3371$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	10102	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 40.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	$M_S = 0.887$	
Space mean speed in ramp influence area,	$S_R = 44.0$	mph
Space mean speed in outer lanes,	$S_0 = 52.1$	mph
Space mean speed for all vehicles,	$S = 47.7$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6960	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	1381	vph
Length of first accel/decel lane	650	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	2774	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	1300	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6960	1381	2774	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1933	384	771	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8429	1673	3360	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.009 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 73 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
v _{FO}		10102	9200	Yes
v ₃ or v _{av34}		4178 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?			Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2			Yes	
If yes, v _{12A} = 3371			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	10102	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 40.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M	= 0.887	
Space mean speed in ramp influence area,	S _R	= 44.0	mph
Space mean speed in outer lanes,	S ₀	= 52.1	mph
Space mean speed for all vehicles,	S	= 47.7	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

-----Merge Analysis-----

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 NB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

-----Freeway Data-----

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	8341	vph

-----On Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1127	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1381	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2800	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	8341	1127	1381	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2317	313	384	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	10102	1365	1673	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.047 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 477 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	11467	9200	Yes
v ₃ or v _{av34}	4812 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		Yes	
If yes, v _{12A} = 4040		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	11467	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 37.6 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M _S = 1.054	
Space mean speed in ramp influence area,	S _R = 41.0	mph
Space mean speed in outer lanes,	S ₀ = 49.1	mph
Space mean speed for all vehicles,	S = 44.9	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

Diverge Analysis

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Road
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7927	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	45.0	mph
Volume on ramp	1138	vph
Length of first accel/decel lane	1400	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	790	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2000	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7927	1138	790	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2202	316	219	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9600	1378	957	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.436 \quad \text{Using Equation 8}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 4963 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	9600	9200	Yes
$v_{FO} = v_F - v_R$	8222	9200	No
v_R	1378	2100	No
v_3 or v_{av34}	2318 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 4963$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	4963	4400	Yes

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 34.3$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence F			

Speed Estimation

Intermediate speed variable,	$D_S = 0.422$	
Space mean speed in ramp influence area,	$S_R = 52.4$	mph
Space mean speed in outer lanes,	$S_0 = 60.7$	mph
Space mean speed for all vehicles,	$S = 56.1$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 6/24/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6789	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	790	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1520	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2760	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6789	790	1520	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1886	219	422	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8222	957	1841	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.593 \quad \text{Using Equation 1}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 4875 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v _{FO}	9179	6900	Yes
v ₃ or v _{av34}	3347 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2		No	
If yes, v _{12A} = 5522		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{12A}	9179	4600	Yes

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 52.1 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

Speed Estimation

Intermediate speed variable,	M _S = 2.828	
Space mean speed in ramp influence area,	S _R = 9.1	mph
Space mean speed in outer lanes,	S ₀ = 51.1	mph
Space mean speed for all vehicles,	S = 12.0	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	6789	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	30.0	mph
Volume on ramp	790	vph
Length of first accel/decel lane	550	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1138	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	2800	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	6789	790	1138	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	1886	219	316	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	8222	957	1378	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 0.098 \quad \text{Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 807 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
v_{FO}	9179	9200	No
v_3 or v_{av34}	3707 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		Yes	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		Yes	
If yes, $v_{12A} = 3288$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v_{12A}	9179	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 34.7 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence D

Speed Estimation

Intermediate speed variable,	$M_S = 0.560$	
Space mean speed in ramp influence area,	$S_R = 49.9$	mph
Space mean speed in outer lanes,	$S_0 = 52.5$	mph
Space mean speed for all vehicles,	$S = 51.3$	mph

Florence & Hutcheson
501 Huger Street
Columbia, SC 29201

Phone: (803)254-5800
E-mail:

Fax: (803)929-0334

_____Merge Analysis_____

Analyst: JP
Agency/Co.: Florence & Hutcheson
Date performed: 4/5/2011
Analysis time period: PM
Freeway/Dir of Travel: I-85 SB
Junction: Pelham Rd
Jurisdiction: Greenville, SC
Analysis Year: 2035
Description: I-85/I-385 No-Build

_____Freeway Data_____

Type of analysis	Merge	
Number of lanes in freeway	4	
Free-flow speed on freeway	60.0	mph
Volume on freeway	7579	vph

_____On Ramp Data_____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1520	vph
Length of first accel/decel lane	1500	ft
Length of second accel/decel lane		ft

_____Adjacent Ramp Data (if one exists)_____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	790	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	On	
Distance to adjacent Ramp	2800	ft

_____Conversion to pc/h Under Base Conditions_____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	7579	1520	790	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	2105	422	219	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	9179	1841	957	pcph

-----Estimation of V12 Merge Areas-----

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = -0.012 \text{ Using Equation 4}$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = -112 \text{ pc/h}$$

-----Capacity Checks-----

	Actual	Maximum	LOS F?
v _{FO}	11020	9200	Yes
v ₃ or v _{av34}	4645 pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?		Yes	
Is v ₃ or v _{av34} > 1.5 v ₁₂ /2		Yes	
If yes, v _{12A} = 3671		(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
v _{12A}	11020	4600	Yes

-----Level of Service Determination (if not F)-----

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 38.2 \text{ pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence F

-----Speed Estimation-----

Intermediate speed variable,	M _S = 1.152	
Space mean speed in ramp influence area,	S _R = 39.3	mph
Space mean speed in outer lanes,	S ₀ = 50.7	mph
Space mean speed for all vehicles,	S = 44.3	mph