

Florence & Hutcheson  
501 Huger Street  
Columbia, SC 29201

Phone: (803)254-5800  
E-mail:

Fax: (803)929-0334

### \_\_\_\_\_Merge Analysis\_\_\_\_\_

Analyst: JP  
Agency/Co.: Florence & Hutcheson  
Date performed: 8/24/2011  
Analysis time period: PM  
Freeway/Dir of Travel: I-85 NB  
Junction: Woodruff NB to I-85NB C-D  
Jurisdiction: Greenville, SC  
Analysis Year: 2035  
Description: I-85/I-385 No-Build

### \_\_\_\_\_Freeway Data\_\_\_\_\_

Type of analysis	Merge	
Number of lanes in freeway	2	
Free-flow speed on freeway	55.0	mph
Volume on freeway	2643	vph

### \_\_\_\_\_On Ramp Data\_\_\_\_\_

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	45.0	mph
Volume on ramp	1665	vph
Length of first accel/decel lane	700	ft
Length of second accel/decel lane		ft

### \_\_\_\_\_Adjacent Ramp Data (if one exists)\_\_\_\_\_

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	1572	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	700	ft

### \_\_\_\_\_Conversion to pc/h Under Base Conditions\_\_\_\_\_

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	2643	1665	1572	vph
Peak-hour factor, PHF	0.90	0.90	0.90	
Peak 15-min volume, v15	734	463	437	v
Trucks and buses	18	18	18	%
Recreational vehicles	0	0	0	%
Terrain type:	Level	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	1.5	1.5	1.5	
Recreational vehicle PCE, ER	1.2	1.2	1.2	

Heavy vehicle adjustment, fHV	0.917	0.917	0.917	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	3201	2017	1904	pcph

-----Estimation of V12 Merge Areas-----

$L =$  (Equation 13-6 or 13-7)  
 $EQ$   
 $P = 1.000$  Using Equation 0  
 $FM$   
 $v_{12} = v_F (P_{FM}) = 3201$  pc/h

-----Capacity Checks-----

	Actual	Maximum	LOS F?
$v_{FO}$	5218	4500	Yes
$v_3$ or $v_{av34}$	0 pc/h	(Equation 13-14 or 13-17)	
Is $v_3$ or $v_{av34} > 2700$ pc/h?		No	
Is $v_3$ or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 3201$		(Equation 13-15, 13-16, 13-18, or 13-19)	

-----Flow Entering Merge Influence Area-----

	Actual	Max Desirable	Violation?
$v_{R12}$	5218	4600	Yes

-----Level of Service Determination (if not F)-----

Density,  $D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 40.9$  pc/mi/ln  
 Level of service for ramp-freeway junction areas of influence F

-----Speed Estimation-----

Intermediate speed variable,	$M_S = 0.978$	
Space mean speed in ramp influence area,	$S_R = 42.3$	mph
Space mean speed in outer lanes,	$S_0 = N/A$	mph
Space mean speed for all vehicles,	$S = 42.3$	mph