

Phone: (803)254-5800

Fax: (803)929-0334

E-mail:

---

 Operational Analysis
 

---

Analyst: NJ  
 Agency/Co.: Florence & Hutcheson  
 Date Performed: 4/4/2011  
 Analysis Time Period: PM  
 Freeway/Dir of Travel: I-85NB C-D  
 Weaving Location: Woodruff & I-385  
 Analysis Year: 2015  
 Description: I-85/I-385 No-Build

---

 Inputs
 

---

|                                |           |         |
|--------------------------------|-----------|---------|
| Segment Type                   | Freeway   |         |
| Weaving configuration          | One-Sided |         |
| Number of lanes, N             | 3         | ln      |
| Weaving segment length, LS     | 840       | ft      |
| Freeway free-flow speed, FFS   | 45        | mi/h    |
| Minimum segment speed, SMIN    | 15        | mi/h    |
| Freeway maximum capacity, cIFL | 2250      | pc/h/ln |
| Terrain type                   | Level     |         |
| Grade                          | 0.00      | %       |
| Length                         | 0.00      | mi      |

---

 Conversion to pc/h Under Base Conditions
 

---

|                                  | Volume Components |       |       |       |       |
|----------------------------------|-------------------|-------|-------|-------|-------|
|                                  | VFF               | VRF   | VFR   | VRR   |       |
| Volume, V                        | 1048              | 670   | 707   | 348   | veh/h |
| Peak hour factor, PHF            | 0.90              | 0.90  | 0.90  | 0.90  |       |
| Peak 15-min volume, v15          | 291               | 186   | 196   | 97    |       |
| Trucks and buses                 | 18                | 18    | 18    | 18    | %     |
| Recreational vehicles            | 0                 | 0     | 0     | 0     | %     |
| Trucks and buses PCE, ET         | 1.5               | 1.5   | 1.5   | 1.5   |       |
| Recreational vehicle PCE, ER     | 1.2               | 1.2   | 1.2   | 1.2   |       |
| Heavy vehicle adjustment, fHV    | 0.917             | 0.917 | 0.917 | 0.917 |       |
| Driver population adjustment, fP | 1.00              | 1.00  | 1.00  | 1.00  |       |
| Flow rate, v                     | 1269              | 811   | 856   | 421   | pc/h  |

Volume ratio, VR 0.497

---

 Configuration Characteristics
 

---

|                                     |      |        |
|-------------------------------------|------|--------|
| Number of maneuver lanes, NWL       | 2    | ln     |
| Interchange density, ID             | 0.00 | int/mi |
| Minimum RF lane changes, LCRF       | 1    | lc/pc  |
| Minimum FR lane changes, LCFR       | 1    | lc/pc  |
| Minimum RR lane changes, LCRR       |      | lc/pc  |
| Minimum weaving lane changes, LCMIN | 1667 | lc/h   |
| Weaving lane changes, LCW           | 1749 | lc/h   |
| Non-weaving vehicle index, INW      | 0    |        |
| Non-weaving lane change, LCNW       | 226  | lc/h   |
| Total lane changes, LCALL           | 1975 | lc/h   |

---

 Weaving and Non-Weaving Speeds
 

---

Weaving intensity factor, W 0.444

|                                |      |      |
|--------------------------------|------|------|
| Average weaving speed, SW      | 35.8 | mi/h |
| Average non-weaving speed, SNW | 27.6 | mi/h |

|   |       |          |
|---|-------|----------|
| _____Weaving Segment Speed, Density, Level of Service and Capacity_____ |       |          |
| Weaving segment speed, S  | 31.2  | mi/h     |
| Weaving segment density, D  | 35.9  | pc/mi/ln |
| Level of service, LOS   | E     |          |
| Weaving segment v/c ratio   | 0.695 |          |
| Weaving segment flow rate, v  | 3357  | pc/h     |
| Weaving segment capacity, cW  | 4434  | veh/h    |

|   |  |  |  |  |
|---|--|--|--|--|
| _____Limitations on Weaving Segments_____ |  |  |  |  |
| If limit reached, see note.               |  |  |  |  |

|  |         |         |          |      |
|--|---------|---------|----------|------|
|  | Minimum | Maximum | Actual   | Note |
| Weaving length (ft)                    | 300     | 7786    | 840      | a,b  |
|  |         | Maximum | Analyzed |      |
| Density-based capacity, cIWL (pc/h/ln) |         | 2250    | 1719     | c    |
|  |         | Maximum | Analyzed |      |
| v/c ratio                              |         | 1.00    | 0.695    | d    |

Notes:

- In weaving segments shorter than 300 ft, weaving vehicles are assumed to make only necessary lane changes.
- Weaving segments longer than the calculated maximum length should be treated as isolated merge and diverge areas using the procedures of Chapter 13, "Freeway Merge and Diverge Segments."
- The density-based capacity exceeds the capacity of a basic freeway segment, under equivalent ideal conditions.
- Volumes exceed the weaving segment capacity. The level of service is F.