

Phone: Fax:  
E-mail:

-----Diverge Analysis-----

Analyst:  
Agency/Co.: Stantec  
Date performed: 11/10/2016  
Analysis time period: 2:00PM-3:00PM  
Freeway/Dir of Travel: I-85 Southbound  
Junction: I-85 SB Off Ramp to SC 5  
Jurisdiction: SCDOT  
Analysis Year: 2040 Build Conditions  
Description:

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	3	
Free-flow speed on freeway	69.4	mph
Volume on freeway	2980	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	178	vph
Length of first accel/decel lane	465	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	343	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2290	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	2980	178	343	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	793	47	91	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4597	189	365	pcph

#### Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.636 \quad \text{Using Equation 5}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 2994 \quad \text{pc/h}$$

#### Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	4597	7182	No
$v_{FO} = v_F - v_R$	4408	7182	No
$v_R$	189	2000	No
$v_3$ or $v_{av34}$	1603 pc/h	(Equation 13-14 or 13-17)	
Is $v_3$ or $v_{av34} > 2700$ pc/h?		No	
Is $v_3$ or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 2994$		(Equation 13-15, 13-16, 13-18, or 13-19)	

#### Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
$v_{12}$	2994	4400	No

#### Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 \frac{L}{D}$	$= 25.8$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence C			

#### Speed Estimation

Intermediate speed variable,	$D_S = 0.445$	
Space mean speed in ramp influence area,	$S_R = 57.2$	mph
Space mean speed in outer lanes,	$S_0 = 73.8$	mph
Space mean speed for all vehicles,	$S = 62.1$	mph