

Phone: Fax:  
E-mail:

### Diverge Analysis

Analyst:  
Agency/Co.: Stantec  
Date performed: 11/9/2016  
Analysis time period: 8:00AM-9:00AM  
Freeway/Dir of Travel: I-85 Northbound  
Junction: I-85 NB Off Ramp to Tribal Rd  
Jurisdiction: SCDOT  
Analysis Year: 2040 Build Conditions  
Description:

### Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	3	
Free-flow speed on freeway	70.3	mph
Volume on freeway	1678	vph

### Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	199	vph
Length of first accel/decel lane	1190	ft
Length of second accel/decel lane		ft

### Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	141	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	1111	ft

### Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1678	199	141	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	446	53	38	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	2588	212	150	pcph

#### Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 0.686 \quad \text{Using Equation 5}$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1841 \quad \text{pc/h}$$

#### Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	2588	7200	No
$v_{FO} = v_F - v_R$	2376	7200	No
$v_R$	212	2000	No
$v_3$ or $v_{av34}$	747 pc/h	(Equation 13-14 or 13-17)	
Is $v_3$ or $v_{av34} > 2700$ pc/h?		No	
Is $v_3$ or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1841$		(Equation 13-15, 13-16, 13-18, or 13-19)	

#### Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
$v_{12}$	1841	4400	No

#### Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 \frac{L}{D}$	$= 9.4$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence A			

#### Speed Estimation

Intermediate speed variable,	$D_S = 0.447$	
Space mean speed in ramp influence area,	$S_R = 57.6$	mph
Space mean speed in outer lanes,	$S_0 = 77.1$	mph
Space mean speed for all vehicles,	$S = 62.2$	mph