

Phone: _____ Fax: _____
 E-mail: _____

_____ Merge Analysis _____

Analyst: _____
 Agency/Co.: Stantec
 Date performed: 11/10/2016
 Analysis time period: 2:00PM-3:00PM
 Freeway/Dir of Travel: I-85 Southbound
 Junction: Welcome Cntr On Ramp to I-85 S
 Jurisdiction: SCDOT
 Analysis Year: 2015 Existing Conditions
 Description: _____

_____ Freeway Data _____

Type of analysis	Merge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	2093	vph

_____ On Ramp Data _____

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	35.0	mph
Volume on ramp	109	vph
Length of first accel/decel lane	875	ft
Length of second accel/decel lane		ft

_____ Adjacent Ramp Data (if one exists) _____

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	139	vph
Position of adjacent Ramp	Downstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	2216	ft

_____ Conversion to pc/h Under Base Conditions _____

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	2093	109	139	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	557	29	37	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	%	%	%	%
Length	mi	mi	mi	mi
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	3229	116	148	pcph

Estimation of V12 Merge Areas

$$L = \text{(Equation 13-6 or 13-7)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FM$$

$$v_{12} = v_F (P_{FM}) = 3229 \quad \text{pc/h}$$

Capacity Checks

		Actual	Maximum	LOS F?
v _{FO}		3345	4788	No
v ₃ or v _{av34}	0	pc/h	(Equation 13-14 or 13-17)	
Is v ₃ or v _{av34} > 2700 pc/h?			No	
Is v ₃ or v _{av34} > 1.5 v ₁₂ / 2			No	
If yes, v _{12A} = 3229			(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Merge Influence Area

	Actual	Max Desirable	Violation?
v _{R12}	3345	4600	No

Level of Service Determination (if not F)

$$\text{Density, } D = 5.475 + 0.00734 v_R + 0.0078 v_{12} - 0.00627 L_A = 26.0 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	M _S = 0.370	
Space mean speed in ramp influence area,	S _R = 59.3	mph
Space mean speed in outer lanes,	S ₀ = N/A	mph
Space mean speed for all vehicles,	S = 59.3	mph