

Phone: Fax:  
E-mail:

### Merge Analysis

Analyst:  
Agency/Co.: Stantec  
Date performed: 11/16/2016  
Analysis time period: 2:00PM-3:00PM  
Freeway/Dir of Travel: I-85 Southbound  
Junction: Blacksburg On Ramp to I-85 SB  
Jurisdiction: SCDOT  
Analysis Year: 2040 Build Conditions  
Description:

### Freeway Data

Type of analysis	Merge	
Number of lanes in freeway	3	
Free-flow speed on freeway	69.8	mph
Volume on freeway	3208	vph

### On Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-flow speed on ramp	35.0	mph
Volume on ramp	380	vph
Length of first accel/decel lane	500	ft
Length of second accel/decel lane		ft

### Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent Ramp	115	vph
Position of adjacent Ramp	Upstream	
Type of adjacent Ramp	Off	
Distance to adjacent Ramp	2560	ft

### Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	3208	380	115	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	853	101	31	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	%	%	%	
Length	mi	mi	mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	4949	404	122	pcph

Estimation of V12 Merge Areas				
L	=	795.74	(Equation 13-6 or 13-7)	
EQ				
P	=	0.591	Using Equation 1	
FM				
v <sub>12</sub>	= v <sub>F</sub> (P <sub>FM</sub> )	=	2927	pc/h

Capacity Checks				
v <sub>FO</sub>		Actual	Maximum	LOS F?
		5353	7194	No
v <sub>3</sub> or v <sub>av34</sub>		2022 pc/h	(Equation 13-14 or 13-17)	
Is v <sub>3</sub> or v <sub>av34</sub>	> 2700 pc/h?		No	
Is v <sub>3</sub> or v <sub>av34</sub>	> 1.5 v <sub>12</sub> /2		Yes	
If yes, v <sub>12A</sub>	= 2927	(Equation 13-15, 13-16, 13-18, or 13-19)		

Flow Entering Merge Influence Area			
v <sub>12A</sub>	Actual	Max Desirable	Violation?
	3331	4600	No

Level of Service Determination (if not F)				
Density, D	=	5.475 + 0.00734 v <sub>R</sub> + 0.0078 v <sub>12</sub> - 0.00627 L <sub>A</sub>	=	28.1 pc/mi/ln
Level of service for ramp-freeway junction areas of influence D				

Speed Estimation			
Intermediate speed variable,	M <sub>S</sub>	=	0.395
Space mean speed in ramp influence area,	S <sub>R</sub>	=	58.8 mph
Space mean speed in outer lanes,	S <sub>0</sub>	=	64.3 mph
Space mean speed for all vehicles,	S	=	60.8 mph