

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 Off Ramp to US 29
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.3	mph
Volume on freeway	1133	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	56	vph
Length of first accel/decel lane	228	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	125	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2738	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1133	56	125	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	301	15	33	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1748	60	133	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P = 1748 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1748	4800	No
$v_{FO} = v_F - v_R$	1688	4800	No
v_R	60	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1748$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1748	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 17.2$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence B			

Speed Estimation

Intermediate speed variable,	$D_S = 0.433$	
Space mean speed in ramp influence area,	$S_R = 58.0$	mph
Space mean speed in outer lanes,	$S_0 = N/A$	mph
Space mean speed for all vehicles,	$S = 58.0$	mph

Phone: _____ Fax: _____
 E-mail: _____

-----Diverge Analysis-----

Analyst: _____
 Agency/Co.: Stantec
 Date performed: 11/9/2016
 Analysis time period: 8:00AM-9:00AM
 Freeway/Dir of Travel: I-85 Southbound
 Junction: I-85 Off Ramp to Tribal Rd
 Jurisdiction: SCDOT
 Analysis Year: 2015 Existing Conditions
 Description: _____

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.0	mph
Volume on freeway	991	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	267	vph
Length of first accel/decel lane	700	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	175	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	1615	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	991	267	175	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	264	71	47	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1529	284	186	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1529 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1529	4780	No
$v_{FO} = v_F - v_R$	1245	4780	No
v_R	284	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1529$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1529	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 11.1$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence B			

Speed Estimation

Intermediate speed variable,	$D_S = 0.454$	
Space mean speed in ramp influence area,	$S_R = 56.8$	mph
Space mean speed in outer lanes,	$S_0 = N/A$	mph
Space mean speed for all vehicles,	$S = 56.8$	mph

Phone: _____ Fax: _____
 E-mail: _____

-----Diverge Analysis-----

Analyst: _____
 Agency/Co.: Stantec
 Date performed: 11/9/2016
 Analysis time period: 8:00AM-9:00AM
 Freeway/Dir of Travel: I-85 Southbound
 Junction: I-85 SB Off Ramp to Welcome Cn
 Jurisdiction: SCDOT
 Analysis Year: 2015 Existing Conditions
 Description: _____

-----Freeway Data-----

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	1098	vph

-----Off Ramp Data-----

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	68	vph
Length of first accel/decel lane	255	ft
Length of second accel/decel lane		ft

-----Adjacent Ramp Data (if one exists)-----

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	175	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	3467	ft

-----Conversion to pc/h Under Base Conditions-----

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1098	68	175	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	292	18	47	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1694	72	186	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1694 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1694	4788	No
$v_{FO} = v_F - v_R$	1622	4788	No
v_R	72	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1694$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1694	4400	No

Level of Service Determination (if not F)

$$\text{Density, } D_R = 4.252 + 0.0086 v_{12} - 0.009 L_D = 16.5 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence B

Speed Estimation

Intermediate speed variable,	$D_S = 0.434$	
Space mean speed in ramp influence area,	$S_R = 57.5$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 57.5$	mph

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 SB Off Ramp to Welcome Cn
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	1098	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	68	vph
Length of first accel/decel lane	255	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	68	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2352	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1098	68	68	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	292	18	18	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1694	72	72	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 1.000 \quad \text{Using Equation } 0$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1694 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1694	4788	No
$v_{FO} = v_F - v_R$	1622	4788	No
v_R	72	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1694$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1694	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$= 16.5$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence B			

Speed Estimation

Intermediate speed variable,	$D_S = 0.434$	
Space mean speed in ramp influence area,	$S_R = 57.5$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 57.5$	mph

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 SB Off Ramp to SC 5
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	1091	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	75	vph
Length of first accel/decel lane	465	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	68	vph
Position of adjacent ramp	Upstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2216	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1091	75	68	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	290	20	18	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1683	80	72	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1683 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1683	4788	No
$v_{FO} = v_F - v_R$	1603	4788	No
v_R	80	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1683$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1683	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$L_D = 14.5$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence B			

Speed Estimation

Intermediate speed variable,	$D_S = 0.435$	
Space mean speed in ramp influence area,	$S_R = 57.5$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 57.5$	mph

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 SB Off Ramp to SC 5
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	1091	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	75	vph
Length of first accel/decel lane	465	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	448	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2290	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1091	75	448	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	290	20	119	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	1683	80	477	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

EQ

$$P = 1.000 \quad \text{Using Equation } 0$$

FD

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 1683 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	1683	4788	No
$v_{FO} = v_F - v_R$	1603	4788	No
v_R	80	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 1683$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	1683	4400	No

Level of Service Determination (if not F)

Density,	$D = 4.252 + 0.0086 v_R - 0.009 L_D$	$L_D = 14.5$	pc/mi/ln
Level of service for ramp-freeway junction areas of influence B			

Speed Estimation

Intermediate speed variable,	$D_S = 0.435$	
Space mean speed in ramp influence area,	$S_R = 57.5$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 57.5$	mph

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 Off Ramp to Blacksburg
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	69.4	mph
Volume on freeway	1471	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	68	vph
Length of first accel/decel lane	164	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	137	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	2560	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1471	68	137	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	391	18	36	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	2269	72	146	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 2269 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	2269	4788	No
$v_{FO} = v_F - v_R$	2197	4788	No
v_R	72	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 2269$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	2269	4400	No

Level of Service Determination (if not F)

$$\text{Density, } D = 4.252 + 0.0086 v_R - 0.009 \frac{L}{D} = 22.3 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	$D_S = 0.434$	
Space mean speed in ramp influence area,	$S_R = 57.5$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 57.5$	mph

Phone: Fax:
E-mail:

Diverge Analysis

Analyst:
Agency/Co.: Stantec
Date performed: 11/9/2016
Analysis time period: 8:00AM-9:00AM
Freeway/Dir of Travel: I-85 Southbound
Junction: I-85 SB Off Ramp to Shelby Hwy
Jurisdiction: SCDOT
Analysis Year: 2015 Existing Conditions
Description:

Freeway Data

Type of analysis	Diverge	
Number of lanes in freeway	2	
Free-flow speed on freeway	70.7	mph
Volume on freeway	1554	vph

Off Ramp Data

Side of freeway	Right	
Number of lanes in ramp	1	
Free-Flow speed on ramp	35.0	mph
Volume on ramp	54	vph
Length of first accel/decel lane	295	ft
Length of second accel/decel lane		ft

Adjacent Ramp Data (if one exists)

Does adjacent ramp exist?	Yes	
Volume on adjacent ramp	332	vph
Position of adjacent ramp	Downstream	
Type of adjacent ramp	On	
Distance to adjacent ramp	1322	ft

Conversion to pc/h Under Base Conditions

Junction Components	Freeway	Ramp	Adjacent Ramp	
Volume, V (vph)	1554	54	332	vph
Peak-hour factor, PHF	0.94	0.94	0.94	
Peak 15-min volume, v15	413	14	88	v
Trucks and buses	30	0	0	%
Recreational vehicles	0	0	0	%
Terrain type:	Rolling	Level	Level	
Grade	0.00 %	0.00 %	0.00 %	
Length	0.00 mi	0.00 mi	0.00 mi	
Trucks and buses PCE, ET	2.5	1.5	1.5	
Recreational vehicle PCE, ER	2.0	1.2	1.2	

Heavy vehicle adjustment, fHV	0.690	1.000	1.000	
Driver population factor, fP	1.00	1.00	1.00	
Flow rate, vp	2397	57	353	pcph

Estimation of V12 Diverge Areas

$$L = \text{(Equation 13-12 or 13-13)}$$

$$EQ$$

$$P = 1.000 \quad \text{Using Equation } 0$$

$$FD$$

$$v_{12} = v_R + (v_F - v_R) P_{FD} = 2397 \quad \text{pc/h}$$

Capacity Checks

	Actual	Maximum	LOS F?
$v_{Fi} = v_F$	2397	4800	No
$v_{FO} = v_F - v_R$	2340	4800	No
v_R	57	2000	No
v_3 or v_{av34}	0 pc/h	(Equation 13-14 or 13-17)	
Is v_3 or $v_{av34} > 2700$ pc/h?		No	
Is v_3 or $v_{av34} > 1.5 v_{12} / 2$		No	
If yes, $v_{12A} = 2397$		(Equation 13-15, 13-16, 13-18, or 13-19)	

Flow Entering Diverge Influence Area

	Actual	Max Desirable	Violation?
v_{12}	2397	4400	No

Level of Service Determination (if not F)

$$\text{Density, } D = 4.252 + 0.0086 v_R - 0.009 L_D = 22.2 \quad \text{pc/mi/ln}$$

Level of service for ramp-freeway junction areas of influence C

Speed Estimation

Intermediate speed variable,	$D_S = 0.433$	
Space mean speed in ramp influence area,	$S_R = 58.3$	mph
Space mean speed in outer lanes,	$S_0 = \text{N/A}$	mph
Space mean speed for all vehicles,	$S = 58.3$	mph