

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: Hampshire to SC 18
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3691	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	982	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2847	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.0	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.30	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	4.0	mi/h
Free-flow speed, FFS	69.5	mi/h

LOS and Performance Measures

Flow rate, vp	2847	pc/h/ln
Free-flow speed, FFS	69.5	mi/h
Average passenger-car speed, S	38.5	mi/h
Number of lanes, N	2	
Density, D	73.9	pc/mi/ln
Level of service, LOS	F	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: SC 18 to Gaffney Ferry Rd
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3578	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	952	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2760	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.0	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.17	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	3.7	mi/h
Free-flow speed, FFS	69.8	mi/h

LOS and Performance Measures

Flow rate, vp	2760	pc/h/ln
Free-flow speed, FFS	69.8	mi/h
Average passenger-car speed, S	41.8	mi/h
Number of lanes, N	2	
Density, D	66.1	pc/mi/ln
Level of service, LOS	F	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: Gaffney Ferry to Frontage Rd
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3588	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	954	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2767	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.0	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.00	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	3.2	mi/h
Free-flow speed, FFS	70.3	mi/h

LOS and Performance Measures

Flow rate, vp	2767	pc/h/ln
Free-flow speed, FFS	70.3	mi/h
Average passenger-car speed, S	41.5	mi/h
Number of lanes, N	2	
Density, D	66.6	pc/mi/ln
Level of service, LOS	F	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: Frontage Rd to Blacksburg Hwy
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3584	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	953	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2764	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.3	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.17	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	3.7	mi/h
Free-flow speed, FFS	69.8	mi/h

LOS and Performance Measures

Flow rate, vp	2764	pc/h/ln
Free-flow speed, FFS	69.8	mi/h
Average passenger-car speed, S	41.6	mi/h
Number of lanes, N	2	
Density, D	66.4	pc/mi/ln
Level of service, LOS	F	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: Blacksburg Hwy to SC 5
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3394	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	903	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2618	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.3	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	0.83	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	2.8	mi/h
Free-flow speed, FFS	70.7	mi/h

LOS and Performance Measures

Flow rate, vp	2618	pc/h/ln
Free-flow speed, FFS	70.7	mi/h
Average passenger-car speed, S	46.7	mi/h
Number of lanes, N	2	
Density, D	56.1	pc/mi/ln
Level of service, LOS	F	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: SC 5 to Tribal Road
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3077	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	818	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2373	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.2	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.00	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	3.2	mi/h
Free-flow speed, FFS	70.3	mi/h

LOS and Performance Measures

Flow rate, vp	2373	pc/h/ln
Free-flow speed, FFS	70.3	mi/h
Average passenger-car speed, S	54.0	mi/h
Number of lanes, N	2	
Density, D	43.9	pc/mi/ln
Level of service, LOS	E	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: Tribal Road to US 29
Jurisdiction: SCDOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3051	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	811	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2353	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.2	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	0.83	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	2.8	mi/h
Free-flow speed, FFS	70.7	mi/h

LOS and Performance Measures

Flow rate, vp	2353	pc/h/ln
Free-flow speed, FFS	70.7	mi/h
Average passenger-car speed, S	54.6	mi/h
Number of lanes, N	2	
Density, D	43.1	pc/mi/ln
Level of service, LOS	E	

Overall results are not computed when free-flow speed is less than 55 mph.

Phone: Fax:
E-mail:

Operational Analysis

Analyst:
Agency or Company: Stantec
Date Performed: 11/9/2016
Analysis Time Period: 2:00PM-3:00PM
Freeway/Direction: I-85 Northbound
From/To: US 29 to NC 216
Jurisdiction: SCDOT/NC DOT
Analysis Year: 2040 No Build Conditions
Description:

Flow Inputs and Adjustments

Volume, V	3054	veh/h
Peak-hour factor, PHF	0.94	
Peak 15-min volume, v15	812	v
Trucks and buses	30	%
Recreational vehicles	0	%
Terrain type:	Rolling	
Grade	-	%
Segment length	-	mi
Trucks and buses PCE, ET	2.5	
Recreational vehicle PCE, ER	2.0	
Heavy vehicle adjustment, fHV	0.690	
Driver population factor, fp	1.00	
Flow rate, vp	2355	pc/h/ln

Speed Inputs and Adjustments

Lane width	11.3	ft
Right-side lateral clearance	6.0	ft
Total ramp density, TRD	1.50	ramps/mi
Number of lanes, N	2	
Free-flow speed:	Base	
FFS or BFFS	75.4	mi/h
Lane width adjustment, fLW	1.9	mi/h
Lateral clearance adjustment, fLC	0.0	mi/h
TRD adjustment	4.5	mi/h
Free-flow speed, FFS	69.0	mi/h

LOS and Performance Measures

Flow rate, vp	2355	pc/h/ln
Free-flow speed, FFS	69.0	mi/h
Average passenger-car speed, S	54.5	mi/h
Number of lanes, N	2	
Density, D	43.2	pc/mi/ln
Level of service, LOS	E	

Overall results are not computed when free-flow speed is less than 55 mph.