



South Carolina
Department of Transportation

955 Park Street
Post Office Box 191
Columbia, South Carolina 29202-0191

Office of the Director
(803) 737-1302 ♦ Fax (803) 737-2038

Deputy Director of Engineering
(803) 737-1314 ♦ Fax (803) 737-2038

Deputy Director of Finance and Administration
(803) 737-1240 ♦ Fax (803) 737-1719

Deputy Director of Mass Transit
(803) 737-9720 ♦ Fax (803) 737-9739

September 11, 1996

INSTRUCTIONAL BULLETIN NO. 96-14 (REVISED)

**Superseded
by 1996-16**

SUBJECT: Reclaiming Existing Roadway Notes

EFFECTIVE DATE: September 10, 1996

SUPERSEDES: Letter dated January 31, 1992 by Road Design Engineer and the Plan Preparation Guide Chapter 4, paragraph 5 "Reclaiming Existing Roadway Notes"

The above subject notes used in the plans have been rewritten in order to clarify their intent. Some resident engineers were not measuring the removed asphalt roadway and the graded area for payment as unclassified excavation. This work was being done incidental to the unclassified excavation instead. It is intended that all asphalt plant mix removed which is less than six inches thick and all grading will be measured and paid for as unclassified excavation.

For Areas With Existing Asphalt Pavement. Remove and dispose of existing asphalt pavement as shown by crosshatched area. Grade area to drain. This work will be measured and paid for as unclassified excavation.

Disturbed areas shall be seeded. Preparation, measurement, and payment for seeding of disturbed areas shall be in accordance with the Standard Specifications.

For Areas With Existing Bituminous Surfacing. Scarify and shape to drain abandoned bituminous surfaced roadway where shown by crosshatched area. This work will be measured and paid for as unclassified excavation.

Disturbed areas shall be seeded. Preparation, measurement, and payment for seeding of disturbed areas shall be in accordance with the Standard Specifications.

APPROVED: _____

E. S. Eargle
Road Design Engineer


January 31, 1992

MEMORANDUM TO: All Roadway Design Managers & Squad Leaders

Subject: Reclaiming Existing Roadway

When the existing roadway, located outside the construction lines, is to be reclaimed, the existing roadway is shown by crosshatching. Usually the old roadway will be required to be reclaimed to blend with its surroundings. When this is required of an existing bituminous surfaced or an asphalt paved roadway, please place on the plan sheet, the appropriate note as shown on the attached sheet.

These notes have been reviewed and approved by the Road Construction Engineer. If you have any questions concerning the above, please let me know. Thank you for your continued cooperation.



E. S. Eargle
Road Engineer-Design

PHR/ESE/dga

*Write (with Bill
to include measurement
& payment*

Typical Section Notes. Typical section notes shall be placed on the profile near the beginning station of the section and on the cross sections under plans to the right side of the beginning station of the section. (Example: Use Typical Section No. 1 from Sta. 0+10 To Sta 17+83.3 as shown on sheet 3).

Mucking Notes. Mucking information should be clearly stated on the profile and quantities shown in the inclusions if not calculated from the cross sections. When mucking is shown on the final cross sections, removal line should be depicted as shown on the Standard Drawing.

Driveway Notes. When the pavement structure for driveways is different from the structure shown on the typical section a note stating the driveway structure shall be placed on the General Note Sheet. See figure 4-E for an example.

5. RECLAIMING EXISTING ROADWAY NOTES

When the existing roadway, located outside the construction lines, is to be reclaimed, the existing roadway is shown by crosshatching. Usually the old roadway will be required to be reclaimed to blend with its surroundings. When this is required of an existing bituminous surfaced or an asphalt paved roadway, please place on the plan sheet, the appropriate note as shown below.

For Areas With Existing Asphalt Pavement. Remove and dispose of existing asphalt pavement as shown by crosshatched area. Grade area to drain. ~~Cost to be included in unit price of unclassified excavation.~~ *This work will be measured and paid for as unclassified excavation.*

Disturbed areas shall be seeded. Preparation, measurement and payment for seeding of disturbed areas shall be in accordance with the Standard Specifications.

For Areas With Existing Bituminous Surfacing. Scarify and shape to drain abandoned bituminous surfaced roadway where shown by crosshatched area. ~~Cost to be included in the unit price of unclassified excavation.~~ *No separate payment will be made for this work but will be measured and paid for as unclassified excavation.*

Disturbed areas shall be seeded. Preparation, measurement and payment for seeding of disturbed area shall be in accordance with the Standard Specifications.

measured as

CONSTRUCTION NOTE: (REMOVAL OF PAVED AREAS). The plans for this project specify that certain existing roadway sections, as shown on the plans by cross hatched areas, are to be removed and disposed of and the area graded for proper drainage. This work shall be paid for at the unit price bid for Unclassified Excavation. The seed bed shall be prepared in accordance with Section 810.15 of the Standard Specifications. Seeding shall be performed, measured and paid for in accordance with Section 810 of the Standard Specifications.

LETTER DATED JAN. 31, '92