

Test Location Information:

Exploration: B-34SCPT Date: 10/22/2008
 Surface El.: 7.8 feet Engineer: RCB
 Test Depth: 44.5 feet
 Test El.: -36.7 feet

Vane and Test Data:

Vane Diameter: 3 5/8 inches Vane Type: Standard Vane
 Vane Constant, k: 0.905 Depth of Vane Tip: 44.5
 Torque Arm Length: 12 inches Depth of Vane Tip Below Bottom of Hole: 18 in.
 Torque Rate - Undisturbed: 0.1 deg/sec
 Torque Rate - Remolded: 0.1 deg/sec

Remolded Condition				Remolded Condition			
Degrees of Rotation	Dial Reading (lbs)	Friction (lbs)	S _u (psf)	Degrees of Rotation	Dial Reading (lbs)	Friction (lbs)	S _u (psf)
1	0	0	0	18		0	0
2	7	0	76	19		0	0
3	7	0	76	20		0	0
4	7	0	76	21		0	0
5	7	0	76	22		0	0
6	7	0	76	23		0	0
7	8	0	87	24		0	0
8	8	0	87	25		0	0
9	8	0	87	26		0	0
10	8	0	87	27		0	0
11	8	0	87	28		0	0
12	8	0	87	29		0	0
13	8	0	87	30		0	0
14	8	0	87	31		0	0
15	8	0	87	32		0	0
16	8	0	87	33		0	0
17	8	0	87	34		0	0
				35		0	0



www.smeinc.com

620 Wando Park Boulevard
 Mt. Pleasant, South Carolina 29464
 Tel 843.884.0005
 Fax 843.881.6149

FIELD VANE SHEAR TEST REPORT | 3 of 3

Project No.: 1131-08-554
 Project Name: Port Access Road
 Location: Charleston, SC
 Client: SCDOT