

**SOUTH CAROLINA DEPARTMENT OF TRANSPORTATION**  
**Encroachment Permit**

Permit No : 217736  
Permit Decision Date : 11/9/2018  
Expiration Date : 11/9/2019

Type  
Permit : COMMUNICATIONS  
(Cable TV, Telephone &  
Other)

Location:

<u>District</u>	<u>Work County</u>	<u>Type</u>	<u>Route</u>	<u>Aux</u>	<u>Begin MP</u>	<u>End MP</u>
1	Lexington, SC	S-	273	None	1.025	0.944
1	Lexington, SC	R-	8060	3E1	0.219	0.335

Contact Information

Applicant: CharterCommunicationsIncdbaTimeWarnerCableSoutheastLLC      Phone:  
Contact: Dawn Baez  
Address: 3347 Platt Springs Rd,  
City: West Columbia      State: SC      Zip: 29170

Comments

Charter project is located approximately 600f southeast of the intersection of Outlet Pointe Blvd and Bush River Rd.

Special Provisions:

0004 - SCDOT SHALL BE NOTIFIED WHEN WORK DEFINED IN THE PERMIT STARTS AS WELL AS WHEN THE WORK IS COMPLETED. REFERENCE SHALL BE MADE BY PERMIT NUMBER.

0101 - SHOULDER SOD DESTROYED BY THIS INSTALLATION TO BE REPLACED FOR THE ENTIRE AREA. THE AREA SHALL BE RE-SHAPED AND ROLLED TO THE CROSS SECTION EXISTING PRIOR TO THIS WORK.

0102 - BORE PITS SHALL BE CLOSED IMMEDIATELY AFTER INSTALLATION.

0103 - THE PROPOSED ENCROACHMENT SHALL BE TRENCHED TO A MINIMUM DEPTH OF 42" BELOW THE CROSS SECTION AS ORIGINALLY CONSTRUCTED.

0107 - TRENCH TO BE PROPERLY BACK-FILLED AND THOROUGHLY TAMPED. THE ENTIRE DISTURBED AREA SHALL BE RE-SHAPED AND DRESSED OUT IN A WORKMANSHIP LIKE MANNER.

0109 - THE BORE SHALL BE MADE BY THE DRY BORE METHOD IN SUCH A MANNER AS NOT TO DISTURB THE PAVEMENT. THE BORE PIT MUST NOT BE CLOSER THAN FIVE (5) FEET FROM THE EDGE OF PAVEMENT. THE BORE DEPTH SHALL BE NOT LESS THAN 48" DEEP AT ANY POINT IN THE BORE. NOTICE SHALL BE GIVEN TO THE DEPARTMENT IMMEDIATELY IF THE BORE TURNS AND DAMANGES THE ROAD.

0112 - ALL WATER METERS, AIR VALVES, ELECTRIC TRANSFORMERS, CATV CONNECTION BOXES, TELEPHONE PEDESTALS, AND/OR OTHER UTILITY/SPLICE BOXES SHALL BE PLACED AT THE RIGHT-OF-WAY LINE.

0120 - RESTORATION OF PAVEMENT, SHOULDERS, DITCHES, ETC., TO BE PERFORMED AS SOON AS POSSIBLE AFTER CONSTRUCTION, OR SCHEDULED SO THAT THE CONSTRUCTION

IS NO FURTHER THAN 2,000 L.F. AHEAD OF COMPLETE RESTORATION.

0123 - ALL WORK PERFORMED IN CONNECTION WITH THIS PERMIT SHALL CONFORM TO THE SCDOT "A POLICY FOR ACCOMODATING UTILITIES ON HIGHWAY RIGHT-OF-WAY" MOST CURRENT EDITION.

0125 - ALL CROSSLINE PIPES ARE TO BE LOCATED AND FLAGGED PRIOR TO BEGINNING OPERATION.

0209 - DISTURBED VEGETATION SHALL BE RESEEDDED ACCORDING TO THE SPECIFICAION FOR HIGHWAY CONSTRUCTION.

0301 - THE DITCHES AND/OR SHOULDERS DISTURBED DURING THE INSTALLATION SHALL BE RE-ESTABLISHED TO PROPER GRADE, ORIGINAL CROSS SECTION, STABILIZED, AND ALL DRAIN PIPES CLEARED.

0302 - NO EXCAVATION SHALL BE LEFT OPEN ALONG HIGHWAY.

0306 - TRAFFIC CONTROL, LIGHTS, SIGNS AND FLAG-MEN WILL BE FURNISHED BY APPLICANT AND WILL CONFORM TO PART VI OF THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES.

0310 - FIELD CHANGES, IF NECESSARY, MUST BE APPROVED IN WRITING BEFORE ACTUAL CONSTRUCTION OF PROPOSED CHANGES.

0311 - SEDIMENT AND EROSION CONTROL DEVICES SHALL BE USED TO MINIMIZE THE MOVEMENT OF SEDIMENT.

0312 - THE PERMITTEE SHALL HOLD THE DEPARTMENT HARMLESS FOR DAMAGES TO BOTH UPSTREAM AND DOWNSTREAM PROPERTIES.

0318 - THE APPLICANT SHALL BE RESPONSIBLE FOR IMMEDIATE REMOVAL OF SUCH TRAFFIC HAZARDS AS MUD, DEBRIS, LOOSE STONE, AND TRASH AS MAY BE WASHED OR SPILLED ON THE TRAVELED ROADWAY AS A RESULT OF THE PROPOSED WORK.

9999 - See Attached for Additional Special Provisions